



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** RTV Silicone Sealant - Blue (pressurized)

**Other means of identification**

**Product code** 14057

**Recommended use** Sealant and adhesive

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service** 800-272-4620

**24-Hour Emergency (CHEMTREC)** 800-424-9300 (US)  
703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

**Physical hazards** Gases under pressure Compressed gas

**Health hazards** Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1

Carcinogenicity Category 2

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Danger

**Hazard statement** Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye damage. Suspected of causing cancer. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

**Response**

If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If exposed or concerned: Get medical attention.

|  |  |
|--|--|
| <b>Storage</b>                                   | Store locked up. Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst. |
| <b>Disposal</b>                                  | Dispose of contents/container in accordance with local/regional/national regulations.  |
| <b>Hazard(s) not otherwise classified (HNOC)</b> | None known.  |

#### Supplemental information

91.75% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 91.75% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. When heated to temperature above 300°F/150°C in the presence of air, product may form formaldehyde vapors. When exposed to water or humid air, product evolves acetic acid (HOAc).

### 3. Composition/information on ingredients

#### Mixtures

| Chemical name                                | Common name and synonyms | CAS number | %       |
|--|--------------------------|------------|---------|
| Polydimethylsiloxane, hydroxy-terminated     |                          | 70131-67-8 | 60 - 70 |
| Amorphous silica                             |                          | 7631-86-9  | 5 - 10  |
| Distillates (petroleum), Hydrotreated Middle |                          | 64742-46-7 | 5 - 10  |
| Polydimethylsiloxane                         |                          | 63148-62-9 | 5 - 10  |
| Aluminium                                    |                          | 7429-90-5  | 1 - 3   |
| Ethyltriacetoxysilane                        |                          | 17689-77-9 | 1 - 3   |
| Methyltriacetoxysilane                       |                          | 4253-34-3  | 1 - 3   |
| Nitrogen                                     |                          | 7727-37-9  | 1 - 3   |
| Titanium dioxide                             |                          | 13463-67-7 | 1 - 3   |
| Carbon black                                 |                          | 1333-86-4  | < 1     |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

|   |   |
|---|---|
| <b>Inhalation</b>   | Move to fresh air. Call a physician if symptoms develop or persist.   |
| <b>Skin contact</b>   | Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.   |
| <b>Eye contact</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.                               |
| <b>Ingestion</b>  | In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.  |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.  |
| <b>General information</b>  | IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.                                   |

### 5. Fire-fighting measures

|  |   |
|--|---|
| <b>Suitable extinguishing media</b>                                  | Dry chemicals. Foam. Water spray. Carbon dioxide (CO2).   |
| <b>Unsuitable extinguishing media</b>                                | Not available.  |
| <b>Specific hazards arising from the chemical</b>                    | Contents under pressure. When heated to temperature above 300°F/150°C in the presence of air, product may form formaldehyde vapors. When exposed to water or humid air, product evolves acetic acid (HOAc). |
| <b>Special protective equipment and precautions for firefighters</b> | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.  |
| <b>Fire-fighting equipment/instructions</b>                          | In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.                       |

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

### Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

### Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components  | Type | Value                 | Form             |
|---|------|-----------------------|------------------|
| Aluminium (CAS 7429-90-5)                                     | PEL  | 5 mg/m <sup>3</sup>   | Respirable dust. |
|   |      | 15 mg/m <sup>3</sup>  | Total dust.      |
| Carbon black (CAS 1333-86-4)                                  | PEL  | 3.5 mg/m <sup>3</sup> |                  |
| Distillates (petroleum), Hydrotreated Middle (CAS 64742-46-7) | PEL  | 5 mg/m <sup>3</sup>   | Mist.            |
| Titanium dioxide (CAS 13463-67-7)                             | PEL  | 15 mg/m <sup>3</sup>  | Total dust.      |

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components                       | Type | Value                 |
|----------------------------------|------|-----------------------|
| Amorphous silica (CAS 7631-86-9) | TWA  | 0.8 mg/m <sup>3</sup> |
|                                  |      | 20 mppcf              |

#### US. ACGIH Threshold Limit Values

| Components                        | Type | Value                | Form                 |
|-----------------------------------|------|----------------------|----------------------|
| Aluminium (CAS 7429-90-5)         | TWA  | 1 mg/m <sup>3</sup>  | Respirable fraction. |
| Carbon black (CAS 1333-86-4)      | TWA  | 3 mg/m <sup>3</sup>  | Inhalable fraction.  |
| Titanium dioxide (CAS 13463-67-7) | TWA  | 10 mg/m <sup>3</sup> |                      |

#### US. NIOSH: Pocket Guide to Chemical Hazards

| Components                | Type | Value               | Form                               |
|---------------------------|------|---------------------|------------------------------------|
| Aluminium (CAS 7429-90-5) | TWA  | 5 mg/m <sup>3</sup> | Welding fume or pyrophoric powder. |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components   | Type   | Value     | Form        |
|--|--|-----------|-------------|
| Amorphous silica (CAS 7631-86-9)   | TWA  | 5 mg/m3   | Respirable. |
|  |  | 10 mg/m3  | Total       |
|  |  | 6 mg/m3   |             |
| Carbon black (CAS 1333-86-4)   | TWA  | 0.1 mg/m3 |             |
| Distillates (petroleum), Hydrotreated Middle (CAS 64742-46-7)                | STEL   | 10 mg/m3  | Mist.       |
|  | TWA  | 5 mg/m3   | Mist.       |
| <b>Biological limit values</b>   | No biological exposure limits noted for the ingredient(s).   |           |             |
| <b>Exposure guidelines</b>   | Occupational Exposure Limits are not relevant to the current physical form of the product.   |           |             |
| <b>Appropriate engineering controls</b>                                      | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. |           |             |
| <b>Individual protection measures, such as personal protective equipment</b> |  |           |             |
| <b>Eye/face protection</b>   | Wear safety glasses with side shields (or goggles).  |           |             |
| <b>Skin protection</b>   |  |           |             |
| <b>Hand protection</b>   | Wear protective gloves such as: Nitrile. Butyl rubber.   |           |             |
| <b>Other</b>   | Wear appropriate chemical resistant clothing.  |           |             |
| <b>Respiratory protection</b>  | If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.   |           |             |
| <b>Thermal hazards</b>   | Wear appropriate thermal protective clothing, when necessary.  |           |             |
| <b>General hygiene considerations</b>  | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.   |           |             |

**9. Physical and chemical properties****Appearance**

|   |                                    |
|---|------------------------------------|
| <b>Physical state</b>                               | Solid.                             |
| <b>Form</b>   | Paste.                             |
| <b>Color</b>  | Blue.                              |
| <b>Odor</b>   | Acetic acid.                       |
| <b>Odor threshold</b>                               | Not available.                     |
| <b>pH</b>   | Not available.                     |
| <b>Melting point/freezing point</b>                 | Not available.                     |
| <b>Initial boiling point and boiling range</b>      | 680 °F (360 °C) estimated          |
| <b>Flash point</b>                                  | > 212 °F (> 100 °C) Tag Closed Cup |
| <b>Evaporation rate</b>                             | Not available.                     |
| <b>Flammability (solid, gas)</b>                    | Not available.                     |
| <b>Upper/lower flammability or explosive limits</b> |                                    |
| <b>Flammability limit - lower (%)</b>               | Not available.                     |
| <b>Flammability limit - upper (%)</b>               | Not available.                     |
| <b>Vapor pressure</b>                               | 620 hPa estimated                  |
| <b>Vapor density</b>                                | Not available.                     |
| <b>Relative density</b>                             | 1.01                               |
| <b>Solubility (water)</b>                           | Not available.                     |

|  |                           |
|--|---------------------------|
| <b>Partition coefficient (n-octanol/water)</b> | Not available.            |
| <b>Auto-ignition temperature</b>               | 500 °F (260 °C) estimated |
| <b>Decomposition temperature</b>               | Not available.            |
| <b>Viscosity (kinematic)</b>                   | Not available.            |
| <b>Percent volatile</b>                        | < 3 %                     |

## 10. Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport.  |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.  |
| <b>Possibility of hazardous reactions</b> | No dangerous reaction known under conditions of normal use.  |
| <b>Conditions to avoid</b>                | Heat, flames and sparks. Avoid temperatures exceeding the flash point. When heated to temperature above 300°F/150°C in the presence of air, product may form formaldehyde vapors. Contact with incompatible materials. When exposed to water or humid air, product evolves acetic acid (HOAc). |
| <b>Incompatible materials</b>             | Strong oxidizing agents. Moist air. Water, moisture.   |
| <b>Hazardous decomposition products</b>   | Carbon oxides. Traces of incompletely burned carbon compounds. Silicone dioxide. Formaldehyde. Metal oxides. Nitrogen oxides (NOx). Chlorine compounds.  |

## 11. Toxicological information

### Information on likely routes of exposure

|                     |   |
|---------------------|---|
| <b>Ingestion</b>    | Expected to be a low ingestion hazard.  |
| <b>Inhalation</b>   | Inhalation of fumes may result in metal fume fever, a flu-like illness with symptoms of metallic taste, fever and chills, aches, chest tightness, and cough. Material is not likely to present an inhalation hazard at ambient conditions. However, if material is heated or high vapor concentrations are attained, central nervous system depression may occur, which is characterized by drowsiness, dizziness, confusion or loss of coordination. |
| <b>Skin contact</b> | Causes skin irritation.   |
| <b>Eye contact</b>  | Causes serious eye damage.  |

**Symptoms related to the physical, chemical and toxicological characteristics** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity** Not available.

| Product                                   | Species | Test Results                     |
|---|---------|----------------------------------|
| RTV Silicone Sealant - Blue (pressurized) |         |                                  |
| <b>Acute</b>                              |         |                                  |
| <i>Inhalation</i>                         |         |                                  |
| LC50                                      | Rabbit  | 309.0909 mg/l, 4 hours estimated |
| <i>Oral</i>                               |         |                                  |
| LD50                                      | Rat     | 32506.5918 mg/kg estimated       |

\* Estimates for product may be based on additional component data not shown.

|  |  |
|--|--|
| <b>Skin corrosion/irritation</b>         | Causes skin irritation.  |
| <b>Serious eye damage/eye irritation</b> | Causes serious eye damage.   |
| <b>Respiratory sensitization</b>         | Not available.   |
| <b>Skin sensitization</b>                | This product is not expected to cause skin sensitization.  |
| <b>Germ cell mutagenicity</b>            | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| <b>Carcinogenicity</b>                   | Suspected of causing cancer.   |

### IARC Monographs. Overall Evaluation of Carcinogenicity

|                                  |   |
|----------------------------------|---|
| Amorphous silica (CAS 7631-86-9) | 3 Not classifiable as to carcinogenicity to humans. |
| Carbon black (CAS 1333-86-4)     | 2B Possibly carcinogenic to humans.                 |

|   |  |
|---|--|
| <b>Reproductive toxicity</b>                              | This product is not expected to cause reproductive or developmental effects. |
| <b>Specific target organ toxicity - single exposure</b>   | Not classified.  |
| <b>Specific target organ toxicity - repeated exposure</b> | Not classified.  |
| <b>Aspiration hazard</b>                                  | Not likely, due to the form of the product.                                  |
| <b>Chronic effects</b>                                    | Prolonged exposure may cause chronic effects.                                |

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

| Product                                   | Species | Test Results   |
|---|---------|--|
| RTV Silicone Sealant - Blue (pressurized) |         |  |
| <b>Aquatic</b>                            |         |  |
| Fish                                      | LC50    | 85.7053 mg/l, 96 hours estimated   |
| <b>Components</b>                         |         |  |
| Aluminium (CAS 7429-90-5)                 |         |  |
| <b>Aquatic</b>                            |         |  |
| Fish                                      | LC50    | Rainbow trout,donaldson trout (Oncorhynchus mykiss)<br>0.16 mg/l, 96 hours |
| Polydimethylsiloxane (CAS 63148-62-9)     |         |  |
| <b>Aquatic</b>                            |         |  |
| Fish                                      | LC50    | Channel catfish (Ictalurus punctatus)<br>2.36 - 4.15 mg/l, 96 hours        |
| Titanium dioxide (CAS 13463-67-7)         |         |  |
| <b>Aquatic</b>                            |         |  |
| Crustacea                                 | EC50    | Water flea (Daphnia magna)<br>> 1000 mg/l, 48 hours                        |
| Fish                                      | LC50    | Mummichog (Fundulus heteroclitus)<br>> 1000 mg/l, 96 hours                 |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** Not available.

**Bioaccumulative potential** Not available.

**Partition coefficient n-octanol / water (log Kow)**

Nitrogen 0.67

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal of waste from residues / unused products** This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

**Hazardous waste code** Not regulated.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

**DOT**

|                                   |   |
|-----------------------------------|---|
| <b>UN number</b>                  | UN1950                                    |
| <b>UN proper shipping name</b>    | Aerosols, non-flammable, Limited Quantity |
| <b>Transport hazard class(es)</b> |   |
| <b>Class</b>                      | 2.2                                       |
| <b>Subsidiary risk</b>            | -   |
| <b>Label(s)</b>                   | 2.2                                       |
| <b>Packing group</b>              | Not applicable.                           |

|                                     |   |
|-------------------------------------|---|
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Special provisions</b>           | Not available.  |
| <b>Packaging exceptions</b>         | 306   |
| <b>Packaging non bulk</b>           | None  |
| <b>Packaging bulk</b>               | None  |

#### IATA

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1950  |
| <b>UN proper shipping name</b>      | Aerosols, non-flammable, Limited Quantity                               |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 2.2   |
| <b>Subsidiary risk</b>              | -   |
| <b>Packing group</b>                | Not applicable.   |
| <b>Environmental hazards</b>        | No.   |
| <b>ERG Code</b>                     | 2L  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Other information</b>            |   |
| <b>Passenger and cargo aircraft</b> | Allowed.  |
| <b>Cargo aircraft only</b>          | Allowed.  |

#### IMDG

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1950  |
| <b>UN proper shipping name</b>      | AEROSOLS, LIMITED QUANTITY  |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 2   |
| <b>Subsidiary risk</b>              | -   |
| <b>Packing group</b>                | Not applicable.   |
| <b>Environmental hazards</b>        |   |
| <b>Marine pollutant</b>             | No.   |
| <b>EmS</b>                          | Not available.  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |

## 15. Regulatory information

---

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

#### **TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

#### **SARA 304 Emergency release notification**

Not regulated.

#### **US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

#### **US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Not listed.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

#### **CERCLA Hazardous Substances: Reportable quantity**

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

#### **Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

#### **Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Section 311/312** Immediate Hazard - Yes  
**Hazard categories** Delayed Hazard - Yes  
 Fire Hazard - No  
 Pressure Hazard - Yes  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**US state regulations****US. New Jersey Worker and Community Right-to-Know Act**

Aluminium (CAS 7429-90-5)  
 Carbon black (CAS 1333-86-4)  
 Nitrogen (CAS 7727-37-9)  
 Titanium dioxide (CAS 13463-67-7)

**US. Massachusetts RTK - Substance List**

Aluminium (CAS 7429-90-5)  
 Amorphous silica (CAS 7631-86-9)  
 Nitrogen (CAS 7727-37-9)  
 Titanium dioxide (CAS 13463-67-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Aluminium (CAS 7429-90-5)  
 Amorphous silica (CAS 7631-86-9)  
 Carbon black (CAS 1333-86-4)  
 Distillates (petroleum), Hydrotreated Middle (CAS 64742-46-7)  
 Nitrogen (CAS 7727-37-9)  
 Titanium dioxide (CAS 13463-67-7)

**US. Rhode Island RTK**

Aluminium (CAS 7429-90-5)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Carbon black (CAS 1333-86-4) Listed: February 21, 2003

**Volatile organic compounds (VOC) regulations****EPA**

**VOC content (40 CFR 51.100(s))** < 3 %

**Consumer products (40 CFR 59, Subpt. C)** Not regulated

**State**

**Consumer products** This product is regulated as a Sealant and Caulking Compound. This product is compliant for use in all 50 states.

**VOC content (CA)** < 3 %

**VOC content (OTC)** < 3 %

**International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | Yes                    |
| Canada               | Domestic Substances List (DSL)   | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                | Existing Chemicals List (ECL)  | Yes                    |
| New Zealand          | New Zealand Inventory  | Yes                    |
| Philippines          | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | Yes                    |

|                             |   |                               |
|-----------------------------|---|-------------------------------|
| <b>Country(s) or region</b> | <b>Inventory name</b>                         | <b>On inventory (yes/no)*</b> |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes                           |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

---

|                            |   |
|----------------------------|---|
| <b>Issue date</b>          | 06-25-2014  |
| <b>Prepared by</b>         | Allison Cho   |
| <b>Version #</b>           | 01  |
| <b>Further information</b> | Not available.  |
| <b>HMIS® ratings</b>       | Health: 2*<br>Flammability: 1<br>Physical hazard: 0<br>Personal protection: B |
| <b>NFPA ratings</b>        | Health: 2<br>Flammability: 1<br>Instability: 0                                |

**NFPA ratings**



**Disclaimer**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.