



# SAFETY DATA SHEET

Issuing Date 30-Sep-2014

Revision Date 30-Sep-2014

Revision Number 0

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

### GHS product identifier

**Product Name** Hi Purity – Texpen

### Other means of identification

**Part Number** White (17463)

**Formula Code** P746 (White)

**UN-Number** UN1263

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Solvent based marker

**Uses advised against** No information available

### Supplier's details

**Supplier Address**  
ITW PRO BRANDS  
805 E. Old 56 Highway  
Olathe, KS 66061  
TEL: 1-800-443-9536

### Emergency telephone number

**Emergency Telephone Number** 800-535-5053 Infotrac

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Serious Eye Damage/Eye Irritation	Category 1
Skin Sensitization	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 2
Aspiration Toxicity	Category 1
Flammable liquids	Category 3

**GHS Label elements, including precautionary statements****Emergency Overview**

<b>Signal Word</b>		<b>Danger</b>	
<b>Hazard Statements</b>			
<ul style="list-style-type: none"> <li>• Causes serious eye damage</li> <li>• May cause an allergic skin reaction</li> <li>• May cause genetic defects</li> <li>• Suspected of causing cancer</li> <li>• May be fatal if swallowed and enters airways</li> <li>• Flammable liquid and vapor.</li> </ul>			
			
<b>Appearance</b>	Opaque white, Thick viscosity,	<b>Physical State</b>	Liquid.
			<b>Odor</b> Mild

**Precautionary Statements****Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Contaminated work clothing should not be allowed out of the workplace.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wear protective gloves/protective clothing/eye protection/face protection.

**General Advice**

- If exposed or concerned: Get medical attention/advice
- Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a POISON CENTER or doctor/physician.

**Skin**

- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Inhalation**

- None

**Ingestion**

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

**Fire**

- In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

**Spills and Leaks**

- None

**Storage**

- Store locked up.
- Store in a well-ventilated place. Keep cool.

**Disposal**

- Dispose of contents/container to an approved waste disposal plant.

**Hazard Not Otherwise Classified (HNOC)**

Not applicable

**Other information**

71.4424% of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Stoddard solvent	8052-41-3	10-30	*
Kaolin	1332-58-7	10-30	*
Titanium dioxide	13463-67-7	10-30	*
Methyl ethyl ketoxime	96-29-7	1-5	*
Silicon dioxide	7631-86-9	1-5	*
Aluminum hydroxide	21645-51-2	1-5	*
Ethylbenzene	100-41-4	0.1-1	*

*\*The exact percentage (concentration) of composition has been withheld as a trade secret.*

### 4. FIRST AID MEASURES

**Description of necessary first-aid measures****General Advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Immediate medical attention is required.

**Skin Contact**

Flush with cool water. If skin irritation persists, call a physician.

**Inhalation**

Move to fresh air. If symptoms persist, call a physician. If breathing is difficult, give oxygen.

**Ingestion**

Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician if necessary

**Protection of First-aiders**

Use personal protective equipment. Remove all sources of ignition.

**Most important symptoms/effects, acute and delayed**

**Most Important Symptoms/Effects** No information available.

**Indication of immediate medical attention and special treatment needed, if necessary****Notes to Physician**

Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical.

**Unsuitable Extinguishing Media** No information available.

#### **Specific Hazards Arising from the Chemical**

May cause sensitization by skin contact. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes.

#### **Explosion Data**

**Sensitivity to Mechanical Impact**

None.

**Sensitivity to Static Discharge**

Yes.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **6. ACCIDENTAL RELEASE MEASURES**

### **Personal precautions, protective equipment and emergency procedures**

#### **Personal Precautions**

Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Stop leak if you can do it without risk.

### **Environmental Precautions**

#### **Environmental Precautions**

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

### **Methods and materials for containment and cleaning up**

#### **Methods for Containment**

Prevent further leakage or spillage if safe to do so.

#### **Methods for Cleaning Up**

Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

## **7. HANDLING AND STORAGE**

### **Precautions for safe handling**

#### **Handling**

Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage**

Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

#### **Incompatible Products**

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

## **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

### **Control parameters**

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
---------------	-----------	----------	------------

Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Kaolin 1332-58-7	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Silicon dioxide 7631-86-9	10 mg/m <sup>3</sup>	20 mppcf TWA; ((80)/(%) SiO <sub>2</sub> ) mg/m <sup>3</sup> )	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m <sup>3</sup> respirable fraction	-	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

*Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:*

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

#### Appropriate engineering controls

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

#### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields. If splashes are likely to occur, wear: Chemical splash goggles.

**Skin and Body Protection** Chemical resistant gloves. Risk of contact: Boots. Apron.

**Respiratory Protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

<b>Physical State</b>	Liquid	<b>Appearance</b>	Opaque white
<b>Odor</b>	Mild	<b>Odor Threshold</b>	Thick viscosity, No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	No data available	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	136.11-251.67 °C / 277-485 °F	None known
Flash Point	40 °C / 104 °F	None known
Evaporation rate	< 1 (BuAc = 1)	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available 7.0	
lower flammability limit	No data available 1.1	
Vapor Pressure	No data available	None known
Vapor Density	> 1 (air = 1)	None known

<b>Specific Gravity</b>	> 1 @ 70°F	None known
<b>Water Solubility</b>	Negligible	None known
<b>Solubility in other solvents</b>	No data available	None known
<b>Partition coefficient: n-octanol/water</b>	No data available	None known
<b>Autoignition Temperature</b>	No data available	None known
<b>Decomposition Temperature</b>	No data available	None known
<b>Viscosity</b>	No data available	None known

**Flammable Properties** Flammable; may be ignited by heat, sparks or flames.

**Explosive Properties** No data available

**Oxidizing Properties** No data available

#### Other information

**VOC Content (%)** P746 White: 29.10%

**VOC (g/l)** P746 White: 374 g/L

## 10. STABILITY AND REACTIVITY

#### Reactivity

No data available.

#### Chemical stability

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### Hazardous Polymerization

Hazardous polymerization does not occur.

#### Conditions to avoid

Heat, flames and sparks. Incompatible products.

#### Incompatible materials

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

#### Hazardous decomposition products

Carbon oxides. Smoke Soot.

## 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal

**Eye Contact** Causes serious eye damage.

**Skin Contact** May cause irritation.

**Ingestion** May be fatal if swallowed and enters airways.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Titanium dioxide	> 10000 mg/kg ( Rat )	-	-

Silicon dioxide	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	>2.2 mg/L ( Rat ) 4 h
Aluminum hydroxide	> 5000 mg/kg ( Rat )	-	-
Ethylbenzene	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** No information available.

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Sensitization** May cause an allergic skin reaction.  
**Mutagenic Effects** May cause genetic defects.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. This product contains titanium dioxide which is classified as an IARC 2B carcinogen based on laboratory studies where animals were exposed to titanium dioxide dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B	-	-
Silicon dioxide		Group 3		
Ethylbenzene	A3	Group 2B		X

**ACGIH: (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC: (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

**OSHA: (Occupational Safety & Health Administration)**

X - Present

**Reproductive Toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Chronic Toxicity** Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands.  
**Target Organ Effects** Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Lungs.  
**Aspiration Hazard** No information available.

**Numerical measures of toxicity - Product****Acute Toxicity** 71.4424% of the mixture consists of ingredient(s) of unknown toxicity.*The following values are calculated based on chapter 3.1 of the GHS document:***LD50 Oral** 8679 mg/kg; Acute toxicity estimate**LD50 Dermal** 10266 mg/kg; Acute toxicity estimate**Inhalation dust/mist** 187 mg/L; Acute toxicity estimate mg/L**12. ECOLOGICAL INFORMATION**

This product contains a chemical which is listed as a marine pollutant according to DOT.

**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl ethyl ketoxime 96-29-7	EC50 72 h: = 83 mg/L (Desmodesmus subspicatus)	LC50 96 h: 777 - 914 mg/L flow-through (Pimephales promelas) LC50 96 h: = 760 mg/L static (Poecilia reticulata) LC50 96 h: 320 - 1000 mg/L static (Leuciscus idus)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	EC50 48 h: = 750 mg/L (Daphnia magna)
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)

Ethylbenzene 100-41-4	EC50 72 h: = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 438 mg/L (Pseudokirchneriella subcapitata) EC50 72 h: 2.6 - 11.3 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 11.0 - 18.0 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 4.2 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: 7.55 - 11 mg/L flow-through (Pimephales promelas) LC50 96 h: = 32 mg/L static (Lepomis macrochirus) LC50 96 h: 9.1 - 15.6 mg/L static (Pimephales promelas) LC50 96 h: = 9.6 mg/L static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h: 1.8 - 2.4 mg/L (Daphnia magna)
--------------------------	---	---	--	--

**Persistence and Degradability** No information available.

#### Bioaccumulation

Chemical Name	Log Pow
Methyl ethyl ketoxime	0.65
Ethylbenzene	3.118

#### Other Adverse Effects

No information available.

### 13. DISPOSAL CONSIDERATIONS

#### Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

#### Contaminated Packaging

Do not re-use empty containers.

#### US EPA Waste Number

D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethylbenzene - 100-41-4		Included in waste stream: F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ethylbenzene	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

**UN-Number** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Marine Pollutant** This product contains a chemical which is listed as a marine pollutant according to DOT.  
**Description** UN1263, Paint, 3, III  
**Emergency Response Guide Number** 128

#### TDG

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263, Paint, 3, III

**MEX**

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Description	UN1263, Paint, 3, III

**ICAO**

UN-Number	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	III
Description	UN1263, Paint, 3, III

**IATA**

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
ERG Code	3L
Description	UN1263, Paint, 3, III

**IMDG/IMO**

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
EmS No.	F-E, S-E
Description	UN1263, Paint, 3, III, (40°C c.c.)

**RID**

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Description	UN1263, Paint, 3, III

**ADR**

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Tunnel Restriction Code	(D/E)
Description	UN1263, Paint, 3, III, (D/E)

**ADN**

Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Special Provisions	163, 640E, 650
Description	UN1263, Paint, 3, III
Limited Quantity	5 L
Ventilation	VE01

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories****Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Ethylbenzene	100-41-4	0.1-1	0.1

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen
Ethylbenzene	100-41-4	Carcinogen
2-Ethylhexanoic acid	149-57-5	Developmental

**U.S. State Right-to-Know Regulations**

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Stoddard solvent	X	X	X		X
Kaolin	X	X	X		X
Titanium dioxide		X			X
Ethylbenzene	X	X	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION**

<b>NFPA</b>	Health Hazard 3	Flammability 2	Instability 0	Physical and Chemical Hazards -
<b>HMIS</b>	Health Hazard 3*	Flammability 2	Physical Hazard 0	Personal Protection X

---

<b>Prepared By</b>	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
<b>Issuing Date</b>	30-Sep-2014
<b>Revision Date</b>	30-Sep-2014
<b>Revision Note</b>	Initial Release.

**General Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**