

Material Safety Data Sheet

ENFORCER

Zep Commercial Sales & Service
A unit of Zep Inc.
1310 Seaboard Industrial Blvd.
Atlanta, GA 30318
1-888-805-HELP (4357)
www.enforcer.com

Section 1. Chemical Product and Company Identification

Product name BugMax Fogger

Product code EBMFOG2

Date of issue 08/26/10 **Supersedes**

EPA Registration Number: 73049-453-40849

Emergency Telephone Numbers

For MSDS Information:

Compliance Services 404-352-1680

For Medical Emergency

(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded

In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
1420 Seaboard Industrial Blvd.
Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

*Hazard Determination System (HDS): Health, Flammability, Reactivity

CAUTION

CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

VAPOR HARMFUL.

CONTENTS UNDER PRESSURE.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Eye contact. Inhalation.

Eyes

Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin

May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.
May cause transient skin sensations (tingling).

Inhalation

Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression.

Ingestion

May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

Chronic effects

Contains material which may cause damage to the following organs: liver.

Carcinogenicity Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Product/ingredient name

ACGIH

IARC

EPA

NIOSH

NTP

OSHA

None.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients

CAS number

% by Weight

BLEND OF ISOBUTANE & PROPANE

74-98-6; 75-28-5

<45

HYDROTREATED LIGHT PETROLEUM DISTILLATES; paraffinic, naphthenic solvent

64742-47-8

1 - 10

Cypermethrin

52315-07-8

0.515

Section 4. First Aid Measures

Eye Contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

Skin Contact

Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Wash clothing before reuse. Get medical attention if irritation develops.

Inhalation


Move exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point	Closed cup: >110°C (>230°F)
Flammable Limits	Not available.
Flammability	Flammable Aerosol propellant.
Fire hazard	CONTENTS UNDER PRESSURE. In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
Fire-Fighting Procedures	Use an extinguishing agent suitable for the surrounding fire. Do not release runoff from fire to drains or watercourses.

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling	Put on appropriate personal protective equipment (see section 8). Observe label precautions. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Empty containers retain product residue and can be hazardous. Apply this product only as specified on the label. Wash thoroughly after handling.
Storage	CONTENTS UNDER PRESSURE. Store and use away from heat, sparks, open flame or any other ignition source. Do not puncture or incinerate container. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection**Product name**

BLEND OF ISOBUTANE & PROPANE

HYDROTREATED LIGHT PETROLEUM DISTILLATES;
paraffinic, naphthenic solvent**Exposure limits**

ACGIH TLV (United States).

TWA: 800 ppm 8 hour(s).

OSHA PEL (United States).

TWA: 1000 ppm 8 hour(s).

Supplier Suggested (United States).

PEL: 100 ppm

ACGIH TLV (United States, 2/2010). Absorbed through skin.

TWA: 200 mg/m³ 8 hour(s).**Personal Protective Equipment (PPE)**

Eyes	Safety glasses.
Body	Recommended: Nitrile gloves. Neoprene gloves.
Respiratory	Avoid direct inhalation of spray. Dangerous fumes are formed during use. Evacuate premises.

Section 9. Physical and Chemical Properties

Physical State	Liquid fill. (Aerosol).	Color	Opaque. White.
pH	Not applicable	Odor	Insecticide.
Boiling Point	Not available.	Vapor Pressure	Not available.
Specific Gravity	0.9604	Vapor Density	>1 [Air = 1]
Solubility	Dispersable in water.	Evaporation Rate	>1 (butyl acetate = 1)
		VOC (Consumer)	< 45%

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Incompatibility	Slightly reactive or incompatible with the following materials: oxidizing materials, acids and alkalis.
Hazardous Polymerization	Will not occur.
Hazardous Decomposition Products	carbon oxides (CO, CO ₂)

Section 11. Toxicological Information**Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Hydrotreated Light Petroleum Distillates	LD50 Dermal	Rabbit	3000 mg/kg	-
Cypermethrin	LC50 Inhalation Vapor	Rat	2.5 g/m3	4 hours
	LD50 Dermal	Rabbit	2460 mg/kg	-
	LD50 Dermal	Rat	>1600 mg/kg	-
	LD50 Oral	Rat	57500 ug/kg	-

Section 12. Ecological Information

Environmental Effects Highly toxic to: Fish, Arthropods

Aquatic Ecotoxicity**Product/ingredient name**

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Non-regulated waste

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not available.	Consumer commodity	ORM-D	-	
TDG Classification		Consumer commodity	ORM-D	-	

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations

California Prop 65 No products were found.

Canada**WHMIS (Canada)**

WHMIS Class A: Compressed gas.

WHMIS Class D-2B: Material causing other toxic effects (Toxic).

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.