

Page 1 of 5

### **CHAMP INVERTED FLUORESCENT PINK**

1. Product And Company Identification		
<u>Supplier</u> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA	<u>Manufacturer</u> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA	
Company Contact: Laura E. Radevski Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com	Company Contact: Laura E. Radevski Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com	
Supplier Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924	Manufacturer Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924	
Chemical Name: 6-6090-3 MSDS Number: 4444 Product Code: 419-4809-8 <u>Product/Material Uses</u> - Spray Paint 2. Composition/Information On Ingredients		
Ingredient	CAS	Percent Of
Name	Number	Total Weight
	67-64-1	
	106-97-8	
CALCIUM CARBONATE ETHYL ALCOHOL	471-34-1	
	8032-32-4	
	64742-95-6	
PROPANE	74-98-6	
V.M. & P. NAPHTHA	64742-89-8	
Hazardous components, according to OSHA, are listed whe present at 0.1% or greater.	en present at 1.0% or greater. Carcinoger	is are listed when

3. Hazards Identification

<u>Primary Routes(s) Of Entry</u> - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. <u>Eye Hazards</u> - Causes eye irritation.

Skin Hazards - Causes skin irritation.

**Ingestion Hazards** - This is an aerosol product, ingestion is unlikely to occur. Contains petroleum distillate, harmful if swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately.

**Inhalation Hazards** - Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea. If dust is formed during use, breathing too much dust may cause irritation of the nose, throat and lungs.

<u>Chronic/Carcinogenicity Effects</u> - Contains less than 1% xylene. Xylene has been associated with kidney and liver disorders. Contains less than 0.1% ethyl benzene; IARC has evaluated and classified ethyl benzene as a possibly human carcinogen (group 2B) based on sufficient evidence of carcinogenicity in animals, but inadequate evidence for cancer in exposed humans. This product may contain up to 0.1% crystalline silica (quartz). California's Proposition 65:

## **CHAMP INVERTED FLUORESCENT PINK**

#### 3. Hazards Identification - Continued

"Warning: This product contains chemicals known to the State of California to cause cancer".

<u>Teratogenicity (Birth Defects)</u> - California Proposition 65: This product may contain chemicals known to the State of California to cause birth defects or other reproductive harm.

Neurotoxicity - Not known

Mutagenicity (Genetic Effect) - Not known

**<u>Signs And Symptoms</u>** - Acute: Prolonged inhalation of vapor or mist may cause headache, dizziness and nausea. Breathing too much dust may cause irritation of the nose, throat and lungs. Prolonged contact with the skin causes irritation. Irritant to eyes.

<u>Conditions Aggravated By Exposure</u> - Pre-existing skin, respiratory, liver and kidney disorders. <u>Conditions Aggravated By Overexposure</u> - Pre-existing skin, respiratory, liver and kidney disorders.

### First Aid (Pictograms)



#### 4. First Aid Measures

**Eye** - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

**<u>Skin</u>** - Wash skin with soap and water. If irritation develops, consult a physician.

**Ingestion** - Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

<u>Inhalation</u> - If overcome by vapor move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

#### 5. Fire Fighting Measures

Flash Point: Not available °F Not available °C Flash Point Method: Not available Lower Explosive Limit: Not available Upper Explosive Limit: Not available

<u>Fire And Explosion Hazards</u> - This product is an aerosol product for which Flame Projection is over 18 in, with flashback. Temperatures above 120 F may cause cans to burst.
 <u>Extinguishing Media</u> - Use CO2 (Carbon Dioxide), dry chemical, or water fog.
 <u>Fire Fighting Instructions</u> - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

#### 6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

### Handling & Storage (Pictograms)



#### 7. Handling And Storage

Handling And Storage Precautions - Handle as an extremely flammable material. Store in a cool, dry place away from heat and open flame.

Handling Precautions - Avoid getting spray into eyes. Keep out of reach of children.

<u>Storage Precautions</u> - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

## CHAMP INVERTED FLUORESCENT PINK

#### 7. Handling And Storage - Continued

**AEROSOL STORAGE LEVEL III (NFPA-30B)** 

Work/Hygienic Practices - Wash hands thoroughly after using this product.

#### Protective Clothing (Pictograms)



#### 8. Exposure Controls/Personal Protection

**Engineering Controls** - Use with adequate general or local exhaust ventilation.

Eve/Face Protection - Conventional eyeglasses to guard against splashing.

<u>Skin Protection</u> - Rubber, vinyl or household type gloves.

**Respiratory Protection** - Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or use an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully.

#### Ingredient(s) - Exposure Limits

ACETONE ACGIH TLV-STEL 750 ppm ; ACGIH TLV-TWA 500 ppm ; OSHA PEL-TWA 1,000 ppm BUTANE ACGIH TLV-TWA 800 ppm CALCIUM CARBONATE ACGIH TLV-TWA 10 mg/m3 ; OSHA PEL-TWA 15 mg/m3 ; OSHA PEL-TWA 5 mg/m3 ETHYL ALCOHOL ACGIH TLV-TWA 1000 ppm ; OSHA PEL-TWA 1000 ppm LIGHT ALIPHATIC NAPHTHA OSHA PEL 400 ppm ; ACGIH TLV 300 ppm LIGHT AROMATIC NAPHTHA 50PPM Recommended by the manufacturer. PROPANE ACGIH TLV-TWA 2500 ppm ; OSHA PEL-TWA 1,000 ppm V.M. & P. NAPHTHA ACGIH TLV-TWA 300 ppm

### 9. Physical And Chemical Properties

<u>Appearance</u> - Appearance of paint. <u>Odor</u> - Paint odor.

Chemical Type: Mixture Physical State: Liquid Melting Point: Not applicable °F Not applicable °C Boiling Point: Water 212 °F Water 100 °C Specific Gravity: 0.948 Percent VOCs: 36.65 Solubility: Insoluble Evaporation Rate: Faster than butyl acetate

## **CHAMP INVERTED FLUORESCENT PINK**

10. Stability And Reactivity
Stability: Stable
Hazardous Polymerization: Will not occur
Conditions To Avaid (Stability) Temperatures above 190 F
Conditions To Avoid (Stability) - Temperatures above 120 F
<b>Incompatible Materials</b> - Avoid heat, open flame and contact with strong oxidizers.
Hazardous Decomposition Products - Thermal decomposition may yield gases like carbon monoxide, carbon
dioxide, nitrogen and sulfur.
Conditions To Avoid (Polymerization) - Temperatures above 120 F
11. Toxicological Information
11. Toxicological Information
No Data Available
12. Ecological Information
<b>Ecotoxicological Information</b> - No specific ecological data is available for this product. Please refer to Section 6 for
information regarding accidental releases and Section 15 for regulatory reporting information.
13. Disposal Considerations
Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call
your local solid waste agency for disposal instructions.
14. Transport Information
Proper Shipping Name - ORM-D Consumer Commodity
Hazard Class
2.1
DOT Identification Number
UN1950
DOT Shipping Label
Aerosol Consumer Commodity
15. Regulatory Information
<b>U.S. Regulatory Information</b> - All ingredients of this product are listed or are excluded from listing under the U.S.
Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
SARA Hazard Classes
SARA Hazard Classes
Acute Health Hazard; Chronic Health Hazard; Fire Hazard
SARA Section 313 Notification - This product does not contain any ingredients (above the <i>de minimis</i> level)
regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.
Ingredient(s) - State Regulations
ACETONE
New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York
City - Hazardous Substance

BUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

CALCIUM CARBONATE Pennsylvania - Workplace Hazard

ETHYL ALCOHOL

## **CHAMP INVERTED FLUORESCENT PINK**

#### 15. Regulatory Information - Continued

#### Ingredient(s) - State Regulations - Continued


New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### V.M. & P. NAPHTHA

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; New York City - Hazardous Substance



#### 16. Other Information

<u>Revision/Preparer Information</u> MSDS Preparer: Laura E. Radevski MSDS Preparer Phone Number: 708-865-1000 This MSDS Supersedes A Previous MSDS Dated: 11/29/2006

#### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

#### Chase Products Co.

Printed Using MSDS Generator™ 2000