

CHAMP PAVE/STRIP FIELD BLACK

1. Product And Company Identification				
<u>Supplier</u> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA	<u>Manufacturer</u> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA			
Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com	Company Contact: Aluc Telephone Number: 70 FAX Number: 708-865-0 E-Mail: sales@chasepro Web Site: www.chasepr	8-865-1000 0923 oducts.com)	θZ
Supplier Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924	Manufacturer Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924			
Issue Date: 08/30/2005 Product Name: CHAMP PAVE/STRIP FIELD BLACK Chemical Name: 6-6102-1 CAS Number: Not Established MSDS Number: 3385 Product Code: 419-4841-2 <u>Product/Material Uses</u> - Spray Paint				
2. Composition/Information On Ingredients				
Ingredient Name		CAS Number		Percent Of Total Weight
BARIUM SULFATE		7727-43-7		
BUTANE		106-97-8		
CARBON BLACK		1333-86-4	<=	1
		8032-32-4		
PROPANE		74-98-6		
		108-88-3		10 - 15
V.M. & P. NAPHTHA		64742-89-8		
XYLENE (MIXED ISOMERS) ZINC SULFIDE		1330-20-7 1314-98-3		1 - 5 1 - 5
Hazardous components, according to OSHA, are listed whe present at 0.1% or greater.	n present at 1.0% or greate		gens	

3. Hazards Identification

<u>**Primary Routes(s) Of Entry</u>** - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. <u>**Eye Hazards**</u> - Causes eye irritation.</u>

Skin Hazards - Causes skin irritation.

Ingestion Hazards - This is an aerosol product, ingestion is unlikely to occur. Contains petroleum distillate, harmful if swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately.

<u>Inhalation Hazards</u> - Deliberate inhalation of concentrate vapor or mist may cause headache, dizziness and nausea.. <u>Chronic/Carcinogenicity Effects</u> - Toluene and xylene have been associated with kidney and liver disorders. Contains less than 1.0% carbon black and less than 0.1% ethyl benzene; IARC has evaluated and classified carbon black and

CHAMP PAVE/STRIP FIELD BLACK

3. Hazards Identification - Continued

ethyl benzene as possibly human carcinogens (group 2B) based on sufficient evidence of carcinogenicity in animals, but inadequate evidence for cancer in exposed humans. Contains less than 0.1% naphthalene. California's Proposition 65: "Warning: This product contains chemicals known to the State of California to cause cancer"

Teratogenicity (Birth Defects) - California's Proposition 65: "Warning: this product contains toluene, a chemical known to the State of California to cause birth defects or other reproductive harm".

<u>**Reproductive Effects</u></u> - Suspect reproductive hazard. Contains material which may cause birth defects, based on animal data. This product contains toluene.</u>**

Neurotoxicity - Not known

Mutagenicity (Genetic Effect) - Not known

<u>Signs And Symptoms</u> - Acute: Prolonged inhalation of vapor or mist may cause headache, dizziness and nausea. Prolonged contact with the skin causes irritation. Irritant to eyes.

Conditions Aggravated By Exposure - Pre-existing skin, respiratory, liver and kidney disorders.

<u>Conditions Aggravated By Overexposure</u> - Pre-existing skin, respiratory, liver and kidney disorders.

First Aid (Pictograms)



4. First Aid Measures

Eye - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

<u>Skin</u> - Wash skin with soap and water. If irritation develops, consult a physician.

Ingestion - Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

Inhalation - If overcome by vapor move victim to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

5. Fire Fighting Measures

Flash Point: Not available °F Not available °C Flash Point Method: Not available Lower Explosive Limit: Not available Upper Explosive Limit: Not available

<u>Fire And Explosion Hazards</u> - This product is an aerosol product for which Flame Projection is over 18 in, with flashback. Temperatures above 120 F may cause cans to burst. <u>Extinguishing Media</u> - Use CO2 (Carbon Dioxide), dry chemical, or water fog. <u>Fire Fighting Instructions</u> - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

Handling & Storage (Pictograms)



CHAMP PAVE/STRIP FIELD BLACK

7. Handling And Storage

Handling And Storage Precautions - Handle as an extremely flammable material. Store in a cool, dry place away from heat and open flame.

Handling Precautions - Avoid getting spray into eyes. Keep out of reach of children.

Storage Precautions - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

AEROSOL STORAGE LEVEL III (NFPA-30B)

Work/Hygienic Practices - Wash hands thoroughly after using this product.

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

Engineering Controls - Use with adequate general and local exhaust ventilation.

Eye/Face Protection - Conventional eyeglasses to guard against splashing.

<u>Skin Protection</u> - Rubber, vinyl or household type gloves.

<u>Respiratory Protection</u> - Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or use an appropriate, properly fitted respiratory (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully.

Ingredient(s) - Exposure Limits

BARIUM SULFATE ACGIH TLV-TWA 10 mg/m3 ; OSHA PEL-TWA 15 mg/m3 ; OSHA PEL-TWA 5 mg/m3 BUTANE ACGIH TLV-TWA 800 ppm CARBON BLACK ACGIH TLV-TWA 3.5 mg/m3; OSHA PEL-TWA 3.5 mg/m3 LIGHT ALIPHATIC NAPHTHA OSHA PEL 400ppm ; ACGIH TLV 300ppm PROPANE ACGIH TLV-TWA 2500 ppm ; OSHA PEL-TWA 1,000 ppm TOLUENE ACGIH TLV-TWA 50 ppm (Skin); OSHA PEL-CEILING 300 ppm; OSHA PEL-PEAK 500 ppm OSHA PEL-TWA 200 ppm V.M. & P. NAPHTHA ACGIH TLV-TWA 300 ppm XYLENE (MIXED ISOMERS) ACGIH TLV-STEL 150 ppm ; ACGIH TLV-TWA 100 ppm ; OSHA PEL-TWA 100 ppm

9. Physical And Chemical Properties

Appearance - Appearance of paint. Odor - Paint odor.

Chemical Type: Mixture Physical State: Liquid Melting Point: Not applicable °F Not applicable °C Boiling Point: Water 212 °F Water 100 °C

CHAMP PAVE/STRIP FIELD BLACK

9. Physical And Chemical Properties - Continued	
Specific Gravity: 1.112 Percent VOCs: 32.68 Solubility: Insoluble Evaporation Rate: Faster than butyl acetate	
I0. Stability And Reactivity	
Stability: Stable Hazardous Polymerization: Will not occur	
Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong oxidizers. Hazardous Decomposition Products - Thermal decomposition may yield gases like carbon monoxide and carbon dioxide. Conditions To Avoid (Polymerization) - Temperatures above 120 F	
11. Toxicological Information	
ngredient(s) - Carginogenicity CARBON BLACK Listed In The IARC Monographs	
12. Ecological Information	
No Data Available	
13. Disposal Considerations	
Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.	
I4. Transport Information	
Proper Shipping Name - ORM-D Consumer Commodity	
Hazard Class 2.1	
DOT Identification Number JN1950	
DOT Shipping Label Aerosol Consumer Commodity	
15. Regulatory Information	
J.S. Regulatory Information - All ingredients of this product are listed or are excluded from listing under the U.S. Foxic Substances Control Act (TSCA) Chemical Substance Inventory.	
SARA Hazard Classes Acute Health Hazard; Chronic Health Hazard; Fire Hazard	
SARA Title III - Section 313 Form "R"/TRI Reportable Chemical	
SARA Section 313 Notification - This product contains the following toxic chemicals (above the de minimis level)	

SARA Section 313 Notification - This product contains the following toxic chemicals (above the *de minimis* level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this

MATERIAL SAFETY DATA SHEET CHAMP PAVE/STRIP FIELD BLACK

15. Regulatory Information - Continued

material. This product contains: Toluene, xylene and zinc sulfide. See section 2 for % amounts in the product.

Ingredient(s) - U.S. Regulatory Information

TOLUENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

XYLENE (MIXED ISOMERS)

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

ZINC SULFIDE SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Reactivity Hazard

Ingredient(s) - State Regulations

BARIUM SULFATE New Jersey - Workplace Hazard

BUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

CARBON BLACK

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance

PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

TOLUENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; California - Proposition 65; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

V.M. & P. NAPHTHA

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; New York City - Hazardous Substance


XYLENE (MIXED ISOMERS)

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

ZINC SULFIDE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard

CHAMP PAVE/STRIP FIELD BLACK



Chase Products Co.

Printed Using MSDS Generator™ 2000