

READERS

All Readers meet or exceed ANSI Z87.1-2003 High Impact Requirements
*CE EN166 Certified *CAN/CSA Z94.3-07
Lenses provide 99% UV protection

VENTURE II® READERS

Available in 3 Lens Colors | Available in 5 Magnifying Strengths



SB1810R10*
Clear +1.0 Lens with Black Frame
SB1810R15**
Clear +1.5 Lens with Black Frame
SB1810R20**
Clear +2.0 Lens with Black Frame
SB1810R25**
Clear +2.5 Lens with Black Frame
SB1810R30*
Clear +3.0 Lens with Black Frame



SB1820R15*
Gray +1.5 Lens with Black Frame
SB1820R20*
Gray +2.0 Lens with Black Frame
SB1820R25*
Gray +2.5 Lens with Black Frame
SB1820R30*
Gray +3.0 Lens with Black Frame



SB1880R15*
Indoor/Outdoor Mirror +1.5 Lens
with Black Frame
SB1880R20*
Indoor/Outdoor Mirror +2.0 Lens
with Black Frame
SB1880R25*
Indoor/Outdoor Mirror +2.5 Lens
with Black Frame

ZTEK® READERS

Available in 3 Magnifying Strengths



S2510R15*
Clear +1.5 Lens with Clear Frame
S2510R20*
Clear +2.0 Lens with Clear Frame
S2510R25*
Clear +2.5 Lens with Clear Frame

INTRUDER® READERS

Available in 3 Magnifying Strengths



S4110R15
Clear +1.5 Lens with Clear Frame
S4110R20
Clear +2.0 Lens with Clear Frame
S4110R25
Clear +2.5 Lens with Clear Frame

ONIX PLUS™ READERS

Exceeds ANSI Z87.1-2003 High Impact Requirements



SB4950PR15 (Anti-Fog)
Clear +1.5 Lens
5.0 IR Filter Flip Lens and Black Frame
SB4950PR20 (Anti-Fog)
Clear +2.0 Lens
5.0 IR Filter Flip Lens and Black Frame



SB4960PR15 (Anti-Fog)
Clear +1.5 Lens
3.0 IR Filter Flip Lens and Black Frame
SB4960PR20 (Anti-Fog)
Clear +2.0 Lens
3.0 IR Filter Flip Lens and Black Frame

www.pyramexsafety.com

Phone 800.736.8673 Fax 901.861.4967



READERS

All Readers meet or exceed ANSI Z87.1-2003 High Impact Requirements
*CE EN166 Certified *CAN/CSA Z94.3-07
Lenses provide 99% UV protection

V2G® READERS

Available in 3 Magnifying Strengths



- GB1810STR15* (Anti-Fog)
Clear +1.5 Lens with Black Strap/Temples
- GB1810STR20* (Anti-Fog)
Clear +2.0 Lens with Black Strap/Temples
- GB1810STR25* (Anti-Fog)
Clear +2.5 Lens with Black Strap/Temples

V2G® Rx INSERTS

Available in 3 Magnifying Strengths



RX1800** Rx Lens Insert

* Take insert to local optometrist
for Rx lens installation.



RX1800R15* Rx Lens Insert with +1.5 Magnification

RX1800R20*
Rx Lens Insert
with +2.0 Magnification

XSG® READERS

Available in 3 Magnifying Strengths



- GB4010STR15* (Anti-Fog)
Clear +1.5 Lens with Black Strap/Temples
- GB4010STR20* (Anti-Fog)
Clear +2.0 Lens with Black Strap/Temples
- GB4010STR25* (Anti-Fog)
Clear +2.5 Lens with Black Strap/Temples

V2G-XP™ Rx INSERT

Exceeds ANSI Z87.1-2003 High Impact Requirements *CAN/CSA Z94.3-07 *CE EN166 Certified




RX6400** Rx Lens Insert

* Take insert to local optometrist
for Rx lens installation.

CAPSTONE 600® Rx INSERT

Exceeds ANSI Z87.1-2003 High Impact Requirements *CAN/CSA Z94.3-07



RX600* Rx Lens Insert

* Take insert to local optometrist
for Rx lens installation.

Insert slides up and down for
perfect placement.

www.pyramexsafety.com

Phone 800.736.8673 Fax 901.861.4967



PYRAMEX