



# Onix Plus™

## SPECIAL FEATURES

- This utility spectacle encompasses ultimate vision protection with a stylish design and various functional features.
- Dual lens and frame with unique outer flip lens system to provide users with multiple options. Flip the outer lens up for general applications. Flip the outer lens down for applications where tinted lenses are needed.
- 3-angle adjustable flip lens allows users to freely adapt to different working procedures.
- Outer flip lens is available in two IR Filter lens options. Ideal for use around welding sites and in cutting and brazing applications.
- Newly designed adjustable nosepiece provides 3 different angles, allowing the user to find the most comfortable fit.
- Co-Material cushioned temple tips provide non-slip comfort
- Lenses filter 99% of harmful UV rays
- Exceeds ANSI Z87.1-2003 High Impact Requirements

## GENERAL SPECIFICATIONS

Lens thickness: 2.20 mm

PD: 68 mm

Lens Base: 8 curve

Weight: 47 gm

Lens size vertical: 45 mm

Lens size diagonal: 141 mm

Bridge: 15 mm

Temple length (lens-tip): 161 mm

Overall Width (hinge-hinge): 128 mm

Closest point between lens: n/a

Closest point between temple tips: 55mm

## FRAME & LENS OPTIONS

- Black Frame with Gray Temples
  - o Clear Anti-fog bottom lens with Gray flip lens; Clear Anti-Fog bottom lens with 5.0 IR filter flip lens; Clear Anti-Fog bottom lens with 3.0 IR filter flip lens

COMPONENT	MATERIAL	FEATURES
Inner Lens	Polycarbonate	Dual 8 base curve lenses
Inner Frame	Polycarbonate	Screwed with outer frame in the front-middle
Outer Lens	Polycarbonate	8 base Curve, Wrap around design w/side protection
Outer frame (nose bridge)	Nylon	Clip-on structure fixes outer lens securely for high impact resistance
Hinge of nose bridge	Polycarbonate	Three lens angle adjustment
Side Shields	Polycarbonate	Integral to lens
Nose Pieces	Bridge – Polycarbonate	Angle adjustable nose piece with co-material soft pad
	Nose Pad – TPE	
Temple	Side arm – Polycarbonate	Spatula, co-material co-injection – durable PC temple w/soft cushion tip
	Tip – TPE	
Ratchets	Nylon	<b>Stationary</b>
Hinge of temple	Polycarbonate	3 Barrel Type, integral to Frame/ratchets
Screw	Stainless Steel	Standard Hinge screw

## MARKINGS:

Lens: As per standard      Frame: As per standard

## PACKAGING:

1 pc in a polybag; 12 pcs in an inner box; 300 pcs in a case

## STANDARDS:

Meets ANSI Z87.1