



Revision Number: 004.0

Issue date: 03/30/2015

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	<b>LOCTITE SF 5408 BELT DRESSING known as LOCTITE BELT DRESSING</b>	<b>IDH number:</b>	226595
<b>Product type:</b>	Coating	<b>Item number:</b>	30527
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	<b>Contact information:</b>	Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**WARNING:** CONTENTS UNDER PRESSURE.  
CAUSES SKIN IRRITATION.  
CAUSES SERIOUS EYE IRRITATION. CONTAINS GAS UNDER PRESSURE;  
MAY EXPLODE IF HEATED.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
GASES UNDER PRESSURE	Liquef. Gas

**PICTOGRAM(S)**



**Precautionary Statements**

<b>Prevention:</b>	Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves.
<b>Response:</b>	IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
<b>Storage:</b>	Protect from sunlight. Store in a well-ventilated place.
<b>Disposal:</b>	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous Component(s)	CAS Number	Percentage*
------------------------	------------	-------------

Ethylbenzene	100-41-4	0.1 - 1
Butane	106-97-8	5 - 10
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Mesitylene	108-67-8	1 - 5
Propane	74-98-6	1 - 5
Solvent naphtha (petroleum), light arom.	64742-95-6	1 - 5

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Wash affected area immediately with soap and water. Remove contaminated clothing and footwear.
<b>Eye contact:</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Get immediate medical attention.
<b>Symptoms:</b>	See Section 11.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Carbon dioxide. Dry chemical. Foam
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.
<b>Unusual fire or explosion hazards:</b>	Contents under pressure. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
<b>Hazardous combustion products:</b>	Oxides of carbon. Irritating vapours.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow material to contaminate ground water system.
<b>Clean-up methods:</b>	Remove all sources of ignition. Maintain good ventilation for large spills. Soak up with inert absorbent. Store in a closed container until ready for disposal.

#### 7. HANDLING AND STORAGE

<b>Handling:</b>	Keep away from heat, spark and flame. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Use only with adequate ventilation.
<b>Storage:</b>	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethylbenzene	20 ppm TWA	100 ppm (435 mg/m <sup>3</sup> ) PEL	None	None
Butane	1,000 ppm STEL	None	None	None
1,2,4-Trimethylbenzene	25 ppm TWA	None	None	None
Mesitylene	25 ppm TWA	None	None	None
Propane	Included in the regulation but with no data values. See regulation for further details	1,000 ppm (1,800 mg/m <sup>3</sup> ) PEL	None	None
Solvent naphtha (petroleum), light arom.	None	None	None	50 ppm

**Engineering controls:**

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s). If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

**Skin protection:**

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid, Aerosol
<b>Color:</b>	Milky, White
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	Not available.
<b>Boiling point/range:</b>	0 - 360 °F (-17.8 - 182.2 °C) None
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	0.92
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	Not applicable to aerosols.
<b>Flashback:</b>	This product exhibits no flashback when tested for flame extension.
<b>Flame projection:</b>	0.00 cm (0inch)
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Not available.
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	17.7 %; 162 g/l
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Irritating fumes.
<b>Incompatible materials:</b>	Strong oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Heat, flames, sparks and other sources of ignition. High temperatures.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

<b>Inhalation:</b>	May cause respiratory tract irritation. Overexposure may cause nervous system depression. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Prolonged exposure to solvents may cause adverse effects to the liver, urinary, and reproductive systems.
<b>Skin contact:</b>	Causes skin irritation.
<b>Eye contact:</b>	Causes serious eye irritation.
<b>Ingestion:</b>	Not a relevant route of exposure.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Ethylbenzene	Oral LD50 (RAT) = 5.46 g/kg Oral LD50 (RAT) = 3,500 mg/kg Dermal LD50 (RABBIT) = 17,800 mg/kg	Irritant, Central nervous system
Butane	Inhalation LC50 (RAT, 4 h) = 658 mg/l	Cardiac, Central nervous system, Irritant
1,2,4-Trimethylbenzene	Oral LD50 (RAT) = 6.0 g/kg Dermal LD50 (RABBIT) = > 3,160 mg/kg Inhalation LC50 (RAT, 48 h) = > 2000 ppm	Central nervous system, Irritant, Respiratory
Mesitylene	None	Central nervous system, Irritant, Respiratory
Propane	Inhalation LC50 (RAT, 15 min) = > 1,442.847 mg/l Inhalation LC50 (RAT, 15 min) = > 1,464 mg/l	Cardiac, Central nervous system, Irritant
Solvent naphtha (petroleum), light arom.	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethylbenzene	No	Group 2B	No
Butane	No	No	No
1,2,4-Trimethylbenzene	No	No	No
Mesitylene	No	No	No
Propane	No	No	No
Solvent naphtha (petroleum), light arom.	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.  
**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Aerosols  
**Hazard class or division:** 2.2  
**Identification number:** UN 1950  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aerosols, non-flammable  
**Hazard class or division:** 2.2  
**Identification number:** UN 1950  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** AEROSOLS  
**Hazard class or division:** 2.2  
**Identification number:** UN 1950  
**Packing group:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None above reporting de minimis  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Immediate Health, Pressure  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 1,2,4-Trimethylbenzene (CAS# 95-63-6). Ethylbenzene (CAS# 100-41-4).  
**CERCLA Reportable quantity:** Butane (CAS# 106-97-8) 100 lbs. (45.4 kg)  
Propane (CAS# 74-98-6) 100 lbs. (45.4 kg)  
**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer.

### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

**Prepared by:** Catherine Bimler, Regulatory Affairs Specialist  
**Issue date:** 03/30/2015

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.