Material Safety Data Sheet





Revision Number: 001.1 Issue date: 05/07/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE® 2 GASKET SEALANT NON- IDH number: 235270

HARDENING PLIABLE SEALANT

Product type:SealantItem number:80964Region:United States

Company address:Contact information:Henkel CorporationTelephone: 860.571.5100

1001 Trout Brook Crossing Emergency telephone: 860.571.5100 Rocky Hill, Connecticut 06067 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW HMIS:

Physical state:PasteHEALTH:*2Color:BlackFLAMMABILITY:1Odor:Ester-likePHYSICAL HAZARD:0

Odor: Ester-like PHYSICAL HAZARD: 0
Personal Protection: See MSDS Section 8

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause irritation to nose and throat. May cause respiratory tract irritation.

Skin contact: May cause allergic skin reaction. May cause skin irritation. Repeated or prolonged contact can

result in drying of skin.

Eye contact: Contact with eyes can cause eye irritation.

Ingestion: Not expected under normal conditions of use. May cause irritation to the gastrointestinal tract,

mouth and mucous membranes.

Existing conditions aggravated by

exposure:

IDH number: 235270

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Al-silicate Kaolin	1332-58-7	30 - 60
Blown castor oil	68187-84-8	10 - 30
Rosin	8050-09-7	10 - 30
Methyl acetate	79-20-9	10 - 30
Titanium dioxide	13463-67-7	1 - 5
Lecithins, soybean	8030-76-0	1 - 5
Quartz (SiO2)	14808-60-7	0.1 - 1
Carbon black	1333-86-4	0.1 - 1

Product name: LOCTITE® 2 GASKET SEALANT NON-HARDENING PLIABLE SEALANT

Page 1 of 5

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. If symptoms

develop and persist, get medical attention.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. Keep individual calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: Product is a solid. (ASTM D 4359)

Autoignition temperature: Not available

Flammable/Explosive limits - lower: Not determined

Flammable/Explosive limits - upper: Not determined

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

IDH number: 235270

Hazardous combustion products: Aldehydes. Oxides of carbon. Carboxylic acids.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Ensure adequate ventilation. Scrape up spilled

material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

For operations where eye or face contact could occur, provide safety shower

and eyewash fountain.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Product name: LOCTITE® 2 GASKET SEALANT NON-HARDENING PLIABLE SEALANT

Page 2 of 5

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Al-silicate Kaolin	2 mg/m3 TWA Respirable fraction.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Blown castor oil	None	None	None	None
Rosin	Included in the regulation but with no data values. See regulation for further details. Exposure by all routes should be carefully controlled to levels as low as possible. (Sensitizer.)	None	None	None
Methyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (610 mg/m3) TWA	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA Total dust.	None	None
Lecithins, soybean	None	None	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None
Carbon black	3.5 mg/m3 TWA	3.5 mg/m3 TWA	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved supplied air respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Butyl rubber gloves. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Color: Black Odor: Ester-like Odor threshold: Not available pH: Not available Vapor pressure: Not available Boiling point/range: Not available Melting point/ range: Not available Specific gravity: Vapor density: 1.55 at 25 °C (77°F) Not available

Flash point: Product is a solid. (ASTM D 4359)

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Not determined
Not available
Not available
Partition coefficient (n-octanol/water):
Not available
0.3 %; 4.65 g/l

IDH number: 235270

Product name: LOCTITE® 2 GASKET SEALANT NON-HARDENING PLIABLE SEALANT Page 3 of 5

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of carbon. Aldehydes. Carboxylic acids.

Incompatible materials: Strong oxidizing agents. Amines. Ammonia. Strong acids. Sulfuric acid. Nitric

acid.

Conditions to avoid: Heat, fumes, sparks and other sources of ignition. Store away from

incompatible materials.

11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 5,000 mg/kg (Estimated)

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Al-silicate Kaolin	No	No	No
Blown castor oil	No	No	No
Rosin	No	No	No
Methyl acetate	No	No	No
Titanium dioxide	No	Group 2B	No
Lecithins, soybean	No	No	No
Quartz (SiO2)	Known carcinogen.	Group 1	No
Carbon black	No	Group 2B	No

Hazardous components	Health Effects/Target Organs
Al-silicate Kaolin	Nuisance dust
Blown castor oil	No Records
Rosin	Respiratory, Irritant, Allergen
Methyl acetate	Blood, Central nervous system, Eyes, Irritant
Titanium dioxide	Irritant, Respiratory
Lecithins, soybean	No Target Organs
Quartz (SiO2)	Immune system, Lung, Some evidence of carcinogenicity
Carbon black	Respiratory, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

IDH number: 235270

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Product name: LOCTITE® 2 GASKET SEALANT NON-HARDENING PLIABLE SEALANT

Page 4 of 5

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

TSCA 12(b) Export Notification: Methyl acetate (CAS# 79-20-9).

CERCLA/SARA Section 302 EHS: None above reporting de minimus CERCLA/SARA Section 311/312: Immediate Health, Delayed Health CERCLA/SARA 313: None above reporting de minimus

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

WHMIS hazard class:

IDH number: 235270

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: LOCTITE® 2 GASKET SEALANT NON-HARDENING PLIABLE SEALANT

Page 5 of 5