



SAFETY DATA SHEET

Issuing Date 16-Sep-2014

Revision Date 16-Sep-2014

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Metal Marking Texpen/Dalo - All colors

Other means of identification

Part Number Black (16030, 16033, 26033), Blue (16013, 26013), Green (16043, 26043), Orange (16103, 26103), Red (16020, 16023, 26023), White (16080, 16083, 16084, 16088, 26083, 26084), Yellow (16060, 16063, 16064, 16068, 26063, 26064)

Formula Code J3070 (Black), J2143 (Blue), Y916 (Green), A451M (Orange), J3076 (Red), J1694 (White), A419M (Yellow)

UN-Number UN1263

Synonyms Texpen - Fine, Medium and Broad
Dalo- Medium and Broad

Recommended use of the chemical and restrictions on use

Recommended Use Solvent based marker

Uses advised against No information available

Supplier's details

Supplier Address
ITW PRO BRANDS
805 E. Old 56 Highway
Olathe, KS 66061
TEL: 1-800-443-9536

Emergency telephone number

Emergency Telephone Number 800-535-5053 Infotrac

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3

Aspiration Toxicity	Category 1
Flammable liquids	Category 3

GHS Label elements, including precautionary statements**Emergency Overview**

Signal Word Danger Hazard Statements • Causes mild skin irritation • May cause genetic defects • Suspected of causing cancer • May cause respiratory irritation • May be fatal if swallowed and enters airways • • Flammable liquid and vapor.		
		
Appearance Opaque, Varies, Thick viscosity,	Physical State Liquid.	Odor Aromatic

Precautionary Statements**Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Keep cool.

General Advice

- If exposed or concerned: Get medical attention/advice

Skin

- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Fire

- In case of fire: Use CO2, dry chemical, or foam for extinction.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Texpen - Fine, Medium and Broad
Dalo- Medium and Broad

Chemical Name	CAS-No	Weight %	Trade secret
Kaolin	1332-58-7	10-30	*
Titanium dioxide	13463-67-7	10-30	*
Petroleum naphtha, light aromatic	64742-95-6	10-30	*
1,2,4 Trimethylbenzene	95-63-6	10-30	*
Carbon black	1333-86-4	1-5	*
1,3,5-Trimethylbenzene	108-67-8	1-5	*
Stoddard solvent	8052-41-3	1-5	*
Xylene, mixed isomers	1330-20-7	1-5	*
Chlorinated hydrocarbons (chlorinated paraffins)	63449-39-8	1-5	*
Cumene	98-82-8	1-5	*
Ethylbenzene	100-41-4	0.1-1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of necessary first-aid measures**

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash skin with soap and water. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician if necessary
Protection of First-aiders	Remove all sources of ignition. Use personal protective equipment.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**Carbon dioxide (CO₂). Foam. Dry chemical.

Unsuitable Extinguishing Media Water.

Specific Hazards Arising from the Chemical

No information available.

Explosion Data**Sensitivity to Mechanical Impact**

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Environmental Precautions**Environmental Precautions**

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. Collect spillage. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up**Methods for Containment**

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

7. HANDLING AND STORAGE**Precautions for safe handling****Handling**

Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Conditions for safe storage, including any incompatibilities**Storage**

Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

Incompatible Products

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
---------------	-----------	----------	------------

Kaolin 1332-58-7	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
1,2,4 Trimethylbenzene 95-63-6	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	TWA: 25 ppm TWA: 125 mg/m ³
Carbon black 1333-86-4	TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
1,3,5-Trimethylbenzene 108-67-8	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	TWA: 25 ppm TWA: 125 mg/m ³
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Xylene, mixed isomers 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Skin and Body Protection Respiratory Protection

If splashes are likely to occur, wear: Chemical splash goggles.
Risk of contact: Apron. Boots. Chemical resistant gloves.
No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State
Odor

Liquid
Aromatic

Appearance
Odor Threshold

Opaque, Varies Thick viscosity,
No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	No data available	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	158.89-170 °C / 318-338 °F	None known
Flash Point	42.22 °C / 108 °F	Tag closed cup
Evaporation rate		None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available 12.3	
lower flammability limit	No data available 1.9	
Vapor Pressure	No data available	None known
Vapor Density	> 1 (air = 1)	None known
Specific Gravity	No data available.	None known
Water Solubility	Slightly soluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Flammable; may be ignited by heat, sparks or flames.

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%)	J3070 Black: 30.97%
	Y916 Green: 30.9%
	J3076 Red: 35.58%
	A419M Yellow: 28.73%
	J2143 Blue: 30.78%
	A451M Orange: 28.97%
	J1694 White: 21.49%
VOC (g/l)	J3070 Black: 382 g/L
	Y916 Green: 375 g/L
	J3076 Red: 430 g/L
	A419M Yellow: 351 g/L
	J2143 Blue: 399 g/L
	A451M Orange: 352 g/L
	J1694 White: 321 g/L

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks. Incompatible products.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

Hazardous decomposition products

Carbon oxides. Smoke Soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information****Inhalation**

May cause irritation of respiratory tract.

Eye Contact

Contact with eyes may cause irritation.

Skin Contact

May cause irritation.

Ingestion

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be fatal if swallowed and enters airways.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
1,2,4 Trimethylbenzene	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Carbon black	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
1,3,5-Trimethylbenzene	= 5000 mg/kg (Rat)	-	= 24 g/m ³ (Rat) 4 h
Xylene, mixed isomers	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 47635 mg/L (Rat) 4 h
Chlorinated hydrocarbons (chlorinated paraffins)	= 26100 mg/kg (Rat)	> 10 mL/kg (Rabbit)	-
Cumene	= 1400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 39000 mg/m ³ (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure**Sensitization**

No information available.

Mutagenic Effects

May cause genetic defects.

Carcinogenicity

May cause cancer. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B	-	-
Carbon black	A3	Group 2B	-	X
Xylene, mixed isomers		Group 3		
Chlorinated hydrocarbons (chlorinated paraffins)		Group 2B		
Cumene		Group 2B		
Ethylbenzene	A3	Group 2B		X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Chronic Toxicity	Avoid repeated exposure. Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. May cause adverse effects on the bone marrow and blood-forming system.
Target Organ Effects	Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Blood. Lungs. Lymphatic system.
Aspiration Hazard	May be fatal if swallowed and enters airways

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral	9951 mg/kg; Acute toxicity estimate
LD50 Dermal	8777 mg/kg; Acute toxicity estimate
Inhalation	mg/L
dust/mist	8 mg/L; Acute toxicity estimate
Vapor	54 mg/L; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum naphtha, light aromatic 64742-95-6		LC50 96 h: = 9.22 mg/L (Oncorhynchus mykiss)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
1,2,4 Trimethylbenzene 95-63-6		LC50 96 h: 7.19 - 8.28 mg/L flow-through (Pimephales promelas) LC50 96 h: = 7.72 mg/L flow-through (Pimephales promelas)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
Carbon black 1333-86-4				EC50 24 h: > 5600 mg/L (Daphnia magna)
1,3,5-Trimethylbenzene 108-67-8		LC50 96 h: = 3.48 mg/L (Pimephales promelas)		EC50 24 h: = 50 mg/L (Daphnia magna)
Xylene, mixed isomers 1330-20-7	EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: 2.661 - 4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 13.1 - 16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: 7.711 - 9.591 mg/L static (Lepomis macrochirus) LC50 96 h: 23.53 - 29.97 mg/L static (Pimephales promelas) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio) LC50 96 h: 30.26 - 40.75 mg/L static (Poecilia reticulata)		EC50 48 h: = 3.82 mg/L (water flea) LC50 48 h: = 0.6 mg/L (Gammarus lacustris)

Chlorinated hydrocarbons (chlorinated paraffins) 63449-39-8		LC50 96 h: 94.5-271 mg/L static (Oncorhynchus mykiss) LC50 96 h: > 0.0109 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: > 0.1 mg/L flow-through (Lepomis macrochirus) LC50 96 h: > 100 mg/L static (Pimephales promelas) LC50 96 h: > 300 mg/L static (Lepomis macrochirus)		EC50 24 h: = 102 mg/L (Daphnia magna)
Cumene 98-82-8	EC50 72 h: = 2.6 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 6.04-6.61 mg/L flow-through (Pimephales promelas) LC50 96 h: = 2.7 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 4.8 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 5.1 mg/L semi-static (Poecilia reticulata)	EC50 = 0.89 mg/L 5 min EC50 = 1.10 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h	EC50 48 h: 7.9 - 14.1 mg/L Static (Daphnia magna) EC50 48 h: = 0.6 mg/L (Daphnia magna)
Ethylbenzene 100-41-4	EC50 72 h: = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 438 mg/L (Pseudokirchneriella subcapitata) EC50 72 h: 2.6 - 11.3 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 11.0 - 18.0 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 4.2 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: 7.55 - 11 mg/L flow-through (Pimephales promelas) LC50 96 h: = 32 mg/L static (Lepomis macrochirus) LC50 96 h: 9.1 - 15.6 mg/L static (Pimephales promelas) LC50 96 h: = 9.6 mg/L static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h: 1.8 - 2.4 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
1,2,4 Trimethylbenzene	3.63
Xylene, mixed isomers	3.15
Chlorinated hydrocarbons (chlorinated paraffins)	6.006
Cumene	3.55
Ethylbenzene	3.118

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number
D001
U055
U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene, mixed isomers - 1330-20-7		Included in waste stream: F039		U239
Cumene - 98-82-8				U055

Ethylbenzene - 100-41-4		Included in waste stream: F039		
-------------------------	--	-----------------------------------	--	--

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Xylene, mixed isomers	Toxic Ignitable
Cumene	Toxic Ignitable
Ethylbenzene	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group III
 Description UN1263, Paint, 3, III, Marine Pollutant
 Emergency Response Guide Number 128

TDG

UN-Number UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III
 Description UN1263, Paint, 3, III, Marine Pollutant

MEX

UN-Number UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III
 Description UN1263, Paint, 3, III

ICAO

UN-Number UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group III
 Description UN1263, Paint, 3, III

IATA

UN-Number UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III
 ERG Code 3L
 Description UN1263, Paint, 3, III

IMDG/IMO

UN-Number UN1263
 Proper Shipping Name Paint
 Hazard Class 3
 Packing Group III
 EmS No. F-E, S-E
 Marine Pollutant Product is a marine pollutant according to the criteria set by IMDG/IMO
 Description UN1263, Paint, 3, III, (42.22°C c.c.), Marine Pollutant

RID

UN-Number UN1263
 Proper Shipping Name Paint

Hazard Class	3
Packing Group	III
Classification Code	F1
Description	UN1263, Paint, 3, III

ADR

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Tunnel Restriction Code	(D/E)
Description	UN1263, Paint, 3, III, (D/E)

ADN

Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III
Classification Code	F1
Special Provisions	163, 640E, 650
Description	UN1263, Paint, 3, III
Limited Quantity	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories**Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene	95-63-6	10-30	1.0
Xylene, mixed isomers	1330-20-7	1-5	1.0
Cumene	98-82-8	1-5	1.0
Ethylbenzene	100-41-4	0.1-1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene, mixed isomers	100 lb			X
Ethylbenzene	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
---------------	--------------------------	------------------------------------	----

Xylene, mixed isomers	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Cumene	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen
Carbon black	1333-86-4	Carcinogen
Chlorinated hydrocarbons (chlorinated paraffins)	63449-39-8	Carcinogen
Cumene	98-82-8	Carcinogen
Ethylbenzene	100-41-4	Carcinogen
Quartz	14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Kaolin	X	X	X		X
Titanium dioxide		X			X
1,2,4 Trimethylbenzene	X	X	X	X	X
Carbon black	X	X	X	X	X
1,3,5-Trimethylbenzene	X	X	X	X	X
Stoddard solvent	X	X	X		X
Xylene, mixed isomers	X	X	X	X	X
Diethylbenzene	X				
Cumene	X	X	X	X	X
Solvent naphtha (petroleum), medium aliphatic	X				
Calcium resinate	X				
Ethylbenzene	X	X	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 2*	Flammability 2	Physical Hazard 0	Personal Protection X

*Indicates a chronic health hazard.

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 16-Sep-2014
Revision Date 16-Sep-2014
Revision Note Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet