# SAFETY DATA SHEET



Issuing Date 16-Sep-2014 Revision Date 16-Sep-2014 Revision Number 0

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

#### **GHS** product identifier

Product Name Sudz Off (Detergent Removable) All Colors

Other means of identification

Part Number Black (44985, 91985), Blue (44938, 91938), Green (44371, 91371), Red (44939, 91939),

White (44146, 91146), Yellow (44694, 91694)

Formula Code Z985 (Black), X938 (Blue), Y371 (Green), X939 (Red), Z146 (White), Z694 (Yellow)

UN-Number UN1263

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Solvent based marker

Uses advised against No information available

Supplier's details

Supplier Address ITW PRO BRANDS 805 E. Old 56 Highway Olathe, KS 66061 TEL: 1-800-443-9536

**Emergency telephone number** 

**Emergency Telephone** 

Number

800-535-5053 Infotrac

## 2. HAZARDS IDENTIFICATION

## Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Acute Oral Toxicity	Category 4
Acute Dermal Toxicity	Category 4
Serious Eye Damage/Eye Irritation	Category 1
Carcinogenicity	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Flammable liquids	Category 3

#### GHS Label elements, including precautionary statements

### **Emergency Overview**

# Signal Word

## **Danger**

# Hazard Statements

- Harmful if swallowed
- Harmful in contact with skin
- Causes serious eye damage
- Suspected of causing cancer
- May cause drowsiness or dizziness
- Flammable liquid and vapor.



Appearance Varies, Thin viscosity,

Physical State Liquid.

Odor Alcohol

#### **Precautionary Statements**

#### Prevention

- · Wash face, hands and any exposed skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- · Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- · Wear eye/face protection.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- · Use only outdoors or in a well-ventilated area.
- · Keep away from heat/sparks/open flames/hot surfaces No smoking.
- · Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- · Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Keep cool.

#### **General Advice**

- Specific measures (see supplemental first aid instructions on this label)
- · If exposed or concerned: Get medical attention/advice

#### Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a POISON CENTER or doctor/physician.

#### Skin

- Call a POISON CENTER or doctor/physician if you feel unwell.
- · Wash contaminated clothing before reuse.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

#### Inhalation

• IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

#### Ingestion

- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- · Rinse mouth.

\_\_\_\_\_

#### Fire

• In case of fire: Use CO2, dry chemical, or foam for extinction.

#### Storage

- · Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

#### Disposa

• Dispose of contents/container to an approved waste disposal plant.

## **Hazard Not Otherwise Classified (HNOC)**

Not applicable

#### Other information

62.2166% of the mixture consists of ingredient(s) of unknown toxicity.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Propanol	71-23-8	60-100	*
Titanium dioxide	13463-67-7	15-40	*
Diacetone alcohol	123-42-2	7-13	*
Silicon dioxide	7631-86-9	3 -7	*
Xanthylium,9-(2-carboxyphenyl)-3,6-bis(diethyl amino)-, hydrogenbis[3-[(4,5-dihydro-3-methyl-5	84962-27-6	1-5	*
Aluminum hydroxide	21645-51-2	1-5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

#### **Description of necessary first-aid measures**

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance. If symptoms persist, call a physician.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Immediate medical attention is required.

**Skin Contact** Flush with cool water. If skin irritation persists, call a physician.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

Ingestion Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Drink plenty of water. Consult a physician if necessary

**Protection of First-aiders**Use personal protective equipment. Remove all sources of ignition.

## Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

## **Suitable Extinguishing Media**

Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical.

Unsuitable Extinguishing Media No information available.

#### **Specific Hazards Arising from the Chemical**

Flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition

**Explosion Data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge Yes.

#### **Protective Equipment and Precautions for Firefighters**

Wear self contained breathing apparatus for fire fighting if necessary.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate

ventilation. Remove all sources of ignition. Stop leak if you can do it without risk.

**Environmental Precautions** 

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system.

#### Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up

the product and place into a container for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handling Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and

sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

#### Conditions for safe storage, including any incompatibilities

Storage Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly

closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container

closed when not in use. Keep away from incompatible materials.

Incompatible Products Strong oxidizing agents. Strong reducing agents. Strong alkalis. Strong acids.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## **Control parameters**

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH

Propanol 71-23-8	TWA: 100 ppm	TWA: 200 ppm TWA: 500 mg/m³ (vacated) TWA: 200 ppm (vacated) TWA: 500 mg/m³ (vacated) STEL: 250 ppm (vacated) STEL: 625 mg/m³	IDLH: 800 ppm TWA: 200 ppm TWA: 500 mg/m³ STEL: 250 ppm STEL: 625 mg/m³
Titanium dioxide 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m³
Diacetone alcohol 123-42-2	TWA: 50 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 240 mg/m³	IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m³
Silicon dioxide 7631-86-9	10 mg/m <sup>3</sup>	20 mppcf TWA; ((80)/(% SiO2) mg/m³)	IDLH: 3000 mg/m³ TWA: 6 mg/m³
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m³ respirable fraction	-	-

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields. If splashes are likely to occur, wear: Chemical splash

goggles.

**Skin and Body Protection** Chemical resistant gloves. Risk of contact: Boots. Apron.

Respiratory Protection No special protective equipment required. If exposure limits are exceeded or irritation is

experienced, NIOSH/MSHA approved respiratory protection should be worn.

**Hygiene Measures** When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area

and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical StateLiquidAppearanceVaries Thin viscosity,OdorAlcoholOdor ThresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks/ - Method</u>

No data available None known pН Melting Point/Range No data available None known **Boiling Point/Boiling Range** 97.22 °C / 207 °F None known 25 °C / 77 °F Flash Point Tag closed cup 1.3 (BuAc = 1)**Evaporation rate** None known Flammability (solid, gas) No data available None known

Flammability Limits in Air

upper flammability limitNo data available 13.7lower flammability limitNo data available 2.1

**Vapor Pressure** No data available None known **Vapor Density** > 1 (air = 1)None known **Specific Gravity** No data available. None known Water Solubility 70-80% None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition Temperature** No data available None known No data available **Decomposition Temperature** None known

No data available

\_\_\_\_\_

None known

**Viscosity** 

\_\_\_\_\_

Flammable Properties Flammable liquid. Flammable; may be ignited by heat, sparks or flames.

**Explosive Properties**No data available **Oxidizing Properties**No data available

**Other information** 

VOC Content (%) Z985 Black: 88%

X939 Red: 92.12% X938 Blue: 89.65% Z146 White: 49.16% Y371 Green: 91.25% Z694 Yellow: 49.22% Z985 Black: 791 g/L

X939 Red: 771 g/L X938 Blue: 737 g/L Z146 White: 564 g/L Y371 Green: 750 g/L

Z694 Yellow: 568 g/L

## **10. STABILITY AND REACTIVITY**

#### Reactivity

VOC (g/I)

No data available.

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### Conditions to avoid

Heat, flames and sparks. Incompatible products.

#### Incompatible materials

Strong oxidizing agents. Strong reducing agents. Strong alkalis. Strong acids.

## **Hazardous decomposition products**

Carbon oxides. Smoke Soot.

## 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

**Product Information** 

Inhalation May cause drowsiness and dizziness. Intentional misuse by deliberately concentrating and

inhaling contents may be harmful or fatal

**Eye Contact** Causes serious eye damage. Causes serious eye irritation.

Skin Contact Harmful in contact with skin.
Ingestion Harmful if swallowed.

Chemical Name	Chemical Name LD50 Oral LD50 Dermal		LC50 Inhalation
Propanol	= 1870 mg/kg (Rat)	= 4049 mg/kg ( Rabbit )	> 13548 ppm (Rat) 4 h
Titanium dioxide	> 10000 mg/kg (Rat)	-	<del>-</del>
Diacetone alcohol	= 4 g/kg (Rat)	= 13500 mg/kg (Rabbit)	-
Silicon dioxide	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>2.2 mg/L (Rat) 4 h
Aluminum hydroxide	> 5000 mg/kg (Rat)	-	-

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

SensitizationNo information available.Mutagenic EffectsNo information available.

Carcinogenicity This product contains titanium dioxide which is classified as an IARC 2B carcinogen based

on laboratory studies where animals were exposed to titanium dioxide dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B	-	-
Silicon dioxide		Group 3		
Xanthylium,9-(2-carboxyphe nyl)-3,6-bis(diethyl amino)-, hydrogenbis[3-[(4,5-dihydro-3-methyl-5		Group 3		

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

**Chronic Toxicity** Avoid repeated exposure. May cause adverse liver effects. May cause adverse effects on

the bone marrow and blood-forming system.

Target Organ Effects Liver. Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Blood.

Gastrointestinal tract (GI). Lungs.

**Aspiration Hazard** No information available.

#### Numerical measures of toxicity - Product

**Acute Toxicity** 62.2166% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

**LD50 Oral** 725 mg/kg; Acute toxicity estimate

LD50 Dermal 1600 mg/kg; Acute toxicity estimate mg/L

#### 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a severe marine pollutant according to DOT.

#### **Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Propanol 71-23-8		LC50 96 h: = 4480 mg/L flow-through (Pimephales promelas)	EC50 = 17700 mg/L 5 min EC50 = 45000 mg/L 5 h EC50 = 8686 mg/L 15 min EC50 = 980 mg/L 12 h	EC50 48 h: = 3642 mg/L (Daphnia magna) EC50 48 h: 3339 - 3977 mg/L Static (Daphnia magna)
Diacetone alcohol 123-42-2		LC50 96 h: = 420 mg/L static (Lepomis macrochirus) LC50 96 h: = 420 mg/L (Lepomis macrochirus)		EC50 24 h: = 8750 mg/L (Daphnia magna)
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)

Persistence and Degradability No information available.

#### **Bioaccumulation**

\_\_\_\_\_

Chemical Name	Log Pow
Propanol	0.25 - 0.34
Diacetone alcohol	1.03

## Other Adverse Effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

**Contaminated Packaging** Do not re-use empty containers.

US EPA Waste Number D001

U239

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste	
Propanol	Toxic	
·	Ignitable	

## 14. TRANSPORT INFORMATION

DOT

UN-Number UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III

Marine Pollutant This product contains a chemical which is listed as a severe marine pollutant according to

DOT.

128

**Description** UN1263, Paint, 3, III

Emergency Response Guide

Number

<u>TDG</u>

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III

**Description** UN1263, Paint, 3, III

MEX

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III

**Description** UN1263, Paint, 3, III

<u>ICAO</u>

UN-Number UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III

**Description** UN1263, Paint, 3, III

IATA

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III
ERG Code 3L

**Description** UN1263, Paint, 3, III

#### IMDG/IMO

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III
EmS No. F-E, S-E

**Description** UN1263, Paint, 3, III, (25°C c.c.)

RID

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group III
Classification Code F1

**Description** UN1263, Paint, 3, III

**ADR** 

UN-Number
Proper Shipping Name
Hazard Class
Packing Group
Classification Code
Tunnel Restriction Code
UN1263
Paint
Baint
Baint
Paint
Bill
Classification Code
F1
CD/E)

**Description** UN1263, Paint, 3, III, (D/E)

ADN

Proper Shipping Name Paint
Hazard Class 3
Packing Group III
Classification Code F1

Special Provisions 163, 640E, 650 Description UN1263, Paint, 3, III

Limited Quantity 5 L Ventilation VE01

## 15. REGULATORY INFORMATION

## **International Inventories**

## Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

## **U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

## Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xanthylium,9-(2-carboxyphe		X		
nyl)-3,6-bis(diethyl amino)-,				
hydrogenbis[3-[(4,5-dihydro-				
3-methyl-5				

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

### **U.S. State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen
Quartz	14808-60-7	Carcinogen

## U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Propanol	Χ	X	X		X
Titanium dioxide		X			X
Diacetone alcohol	Χ	X	X		X
Silicon dioxide	Χ	X	X		
Xanthylium,9-(2-carboxyphe nyl)-3,6-bis(diethyl amino)-, hydrogenbis[3-[(4,5-dihydro- 3-methyl-5			Х	Х	

#### U.S. EPA Label Information

**EPA Pesticide Registration Number** Not applicable

16. OTHER INFORMATION				
NFPA	Health Hazard 3	Flammability 3	Instability 0	Physical and Chemical Hazards -
<u>HMIS</u>	Health Hazard 3*	Flammability 3	Physical Hazard 0	Personal Protection X

<sup>\*</sup>Indicates a chronic health hazard.

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date16-Sep-2014Revision Date16-Sep-2014Revision NoteInitial Release.

## **General Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**