

## **CHAMP PAVE/STRIP HIGHWAY WHITE**

Supplier Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA	Manufacturer Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA			
Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com	Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com Manufacturer Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924			
Supplier Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924				
Product Name: CHAMP PAVE/STRIP HIGHWAY WHIT Chemical Name: 6-6094-1 CAS Number: Not Established MSDS Number: 3482	ΓE			
Product Code: 419-4835-4 Product/Material Uses - Spray Paint 2. Composition/Information On Ingredients				
Product/Material Uses - Spray Paint 2. Composition/Information On Ingredients Ingredient	CA	-		Percent Of
Product/Material Uses - Spray Paint 2. Composition/Information On Ingredients Ingredient Name	Num	ber		Percent Of Total Weight
Product/Material Uses - Spray Paint 2. Composition/Information On Ingredients Ingredient Name BARIUM SULFATE	Num 772	iber 7-43-7		
Product/Material Uses - Spray Paint 2. Composition/Information On Ingredients Ingredient Name BARIUM SULFATE BUTANE	Num 772 10	ber 7-43-7 6-97-8		
Product/Material Uses       - Spray Paint         2. Composition/Information On Ingredients         Ingredient         Name         BARIUM SULFATE         BUTANE         HEAVY AROMATIC NAPHTHA	Num 772 10 6474	ber 7-43-7 6-97-8 2-94-5		
Product/Material Uses - Spray Paint 2. Composition/Information On Ingredients Ingredient Name BARIUM SULFATE BUTANE HEAVY AROMATIC NAPHTHA	Num 772 10 6474 803	ber 7-43-7 6-97-8		
Product/Material Uses       - Spray Paint         2. Composition/Information On Ingredients         Ingredient         Name         BARIUM SULFATE         BUTANE         HEAVY AROMATIC NAPHTHA         LIGHT ALIPHATIC NAPHTHA	Num           772           10           6474           803           805	ber 7-43-7 6-97-8 2-94-5 2-32-4		Total Weight
Product/Material Uses       - Spray Paint         2. Composition/Information On Ingredients         Ingredient         Name         BARIUM SULFATE         BUTANE         HEAVY AROMATIC NAPHTHA         LIGHT ALIPHATIC NAPHTHA         MINERAL SPIRITS	Num           772           10           6474           803           805           9	ber 7-43-7 6-97-8 2-94-5 2-32-4 2-41-3	=	Total Weight
Product/Material Uses       - Spray Paint         2. Composition/Information On Ingredients         Ingredient         Name         BARIUM SULFATE         BUTANE         HEAVY AROMATIC NAPHTHA         LIGHT ALIPHATIC NAPHTHA         MINERAL SPIRITS         NAPHTHALENE	Num           772           10           6474           803           805           9           7.	ber           7-43-7           6-97-8           2-94-5           2-32-4           2-41-3           1-20-3	=	
Product/Material Uses       - Spray Paint         2. Composition/Information On Ingredients         Ingredient         Name         BARIUM SULFATE         BUTANE         HEAVY AROMATIC NAPHTHA         LIGHT ALIPHATIC NAPHTHA         MINERAL SPIRITS         NAPHTHALENE         PROPANE	Num           772           10           6474           803           805           9           7           10           10	ber       7-43-7       6-97-8       2-94-5       2-32-4       2-41-3       1-20-3       4-98-6	=	Total Weight
Product/Material Uses       - Spray Paint         2. Composition/Information On Ingredients         Ingredient         Name         BARIUM SULFATE         BUTANE         HEAVY AROMATIC NAPHTHA         LIGHT ALIPHATIC NAPHTHA         MINERAL SPIRITS         NAPHTHALENE         PROPANE         TOLUENE	Num           772           10           6474           803           805           9           7           10           6474	ber       7-43-7       6-97-8       2-94-5       2-32-4       2-41-3       1-20-3       4-98-6       8-88-3	=	Total Weight

Hazardous components, according to OSHA, are listed when present at 1.0% or greater. Carcinogens are listed when present at 0.1% or greater.

### 3. Hazards Identification

**<u>Primary Routes(s) Of Entry</u>** - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. **Eye Hazards** - Causes eye irritation. **Skin Hazards** - Causes skin irritation.

Ingestion Hazards - This is an aerosol product, ingestion is unlikely to occur. Contains petroleum distillate, harmful if swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately.

**CHAMP PAVE/STRIP HIGHWAY WHITE** 

### 3. Hazards Identification - Continued

**Inhalation Hazards** - Deliberate inhalation of concentrate vapor or mist may cause headache, dizziness and nausea.. **Chronic/Carcinogenicity Effects** - Toluene and xylene have been associated with kidney and liver disorders. Contains less than 0.1% ethyl benzene; IARC has evaluated and classified ethyl benzene as a possible human carcinogen (group 2B) based on sufficient evidence of carcinogenicity in animals, but inadequate evidence for cancer in exposed humans. Contains naphthalene (from heavy aromatic naphtha). California's Proposition 65: "Warning: This product contains chemicals known to the State of California to cause cancer"

**Teratogenicity (Birth Defects)** - California's Proposition 65: "Warning: this product contains toluene, a chemical known to the State of California to cause birth defects or other reproductive harm".

<u>**Reproductive Effects</u></u> - Suspect reproductive hazard. Contains material which may cause birth defects, based on animal data. This product contains toluene.</u>** 

Neurotoxicity - Not known

Mutagenicity (Genetic Effect) - Not known

<u>Signs And Symptoms</u> - Acute: Prolonged inhalation of vapor or mist may cause headache, dizziness and nausea. Prolonged contact with the skin causes irritation. Irritant to eyes.

**Conditions Aggravated By Exposure** - Pre-existing skin, respiratory, liver and kidney disorders.

Conditions Aggravated By Overexposure - Pre-existing skin, respiratory, liver and kidney disorders.

### First Aid (Pictograms)



### 4. First Aid Measures

**Eye** - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin - Wash skin with soap and water. If irritation develops, consult a physician.

**Ingestion** - Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

<u>Inhalation</u> - If overcome by vapor move victim to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

### 5. Fire Fighting Measures

Flash Point: Not available °F Not available °C Flash Point Method: Not available Lower Explosive Limit: Not available Upper Explosive Limit: Not available

<u>Fire And Explosion Hazards</u> - This product is an aerosol product for which Flame Projection is over 18 in, with flashback. Temperatures above 120 F may cause cans to burst.

Extinguishing Media - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

Fire Fighting Instructions - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

### 6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

**CHAMP PAVE/STRIP HIGHWAY WHITE** 

Handling & Storage (Pictograms)



7. Handling And Storage

Handling And Storage Precautions - Handle as an extremely flammable material. Store in a cool, dry place away from heat and open flame.

Handling Precautions - Avoid getting spray into eyes. Keep out of reach of children.

<u>Storage Precautions</u> - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

AEROSOL STORAGE LEVEL III (NFPA-30B)

Work/Hygienic Practices - Wash hands thoroughly after using this product.

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

**Engineering Controls** - Use with adequate general and local exhaust ventilation.

**Eye/Face Protection** - Conventional eyeglasses to guard against splashing.

<u>Skin Protection</u> - Rubber, vinyl or household type gloves.

<u>Respiratory Protection</u> - Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or use an appropriate, properly fitted respiratory (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully.

### Ingredient(s) - Exposure Limits

BARIUM SULFATE ACGIH TLV-TWA 10 mg/m3; OSHA PEL-TWA 15 mg/m3; OSHA PEL-TWA 5 mg/m3 BUTANE ACGIH TLV-TWA 800 ppm HEAVY AROMATIC NAPHTHA OSHA PEL 100 ppm LIGHT ALIPHATIC NAPHTHA OSHA PEL 400ppm ; ACGIH TLV 300ppm MINERAL SPIRITS OSHA PEL 100ppm ; ACGIH TLV 100ppm NAPHTHALENE ACGIH TLV-STEL 15 ppm ; ACGIH TLV-TWA 10 ppm ; OSHA PEL-TWA 10 ppm PROPANE ACGIH TLV-TWA 2500 ppm ; OSHA PEL-TWA 1,000 ppm TOLUENE ACGIH TLV-TWA 50 ppm (Skin); OSHA PEL-CEILING 300 ppm; OSHA PEL-PEAK 500 ppm OSHA PEL-TWA 200 ppm V.M. & P. NAPHTHA ACGIH TLV-TWA 300 ppm XYLENE (MIXED ISOMERS)

### CHAMP PAVE/STRIP HIGHWAY WHITE

### 8. Exposure Controls/Personal Protection - Continued

### Ingredient(s) - Exposure Limits - Continued

ACGIH TLV-STEL 150 ppm ; ACGIH TLV-TWA 100 ppm ; OSHA PEL-TWA 100 ppm

### 9. Physical And Chemical Properties

<u>Appearance</u> - Appearance of paint. <u>Odor</u> - Paint odor.

Chemical Type: Mixture Physical State: Liquid Melting Point: Not applicable °F Not applicable °C Boiling Point: Water 212 °F Water 100 °C Specific Gravity: 1.15 Percent VOCs: 31.16 Solubility: Insoluble Evaporation Rate: Faster than butyl acetate

### **10. Stability And Reactivity**

Stability: Stable Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability) - Temperatures above 120 F

**Incompatible Materials** - Avoid heat, open flame and contact with strong oxidizers.

<u>Hazardous Decomposition Products</u> - Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

Conditions To Avoid (Polymerization) - Temperatures above 120 F

### 11. Toxicological Information

No Data Available...

### 12. Ecological Information

**Ecotoxicological Information** - No specific ecological data is available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

#### 13. Disposal Considerations

Do not puncture or incinerate container. **If empty:** Place in trash or offer for recycling if available. **If partly filled:** Call your local solid waste agency for disposal instructions.

#### 14. Transport Information

Proper Shipping Name - ORM-D Consumer Commodity

Hazard Class

2.1

DOT Identification Number UN1950

DOT Shipping Label Aerosol Consumer Commodity

## CHAMP PAVE/STRIP HIGHWAY WHITE

### 15. Regulatory Information

**U.S. Regulatory Information** - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

### SARA Hazard Classes

Acute Health Hazard; Chronic Health Hazard; Fire Hazard

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

**SARA Section 313 Notification** - This product contains the following toxic chemicals (above the *de minimis* level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material. This product contains: Naphthalene, toluene, xylene and zinc sulfide. See section 2 for % amounts in the product.

### Ingredient(s) - U.S. Regulatory Information

NAPHTHALENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

### TOLUENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

### XYLENE (MIXED ISOMERS)

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

ZINC SULFIDE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Reactivity Hazard

### Ingredient(s) - State Regulations

BARIUM SULFATE New Jersey - Workplace Hazard

#### BUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

### NAPHTHALENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

### TOLUENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; California - Proposition 65; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

V.M. & P. NAPHTHA New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; New York City - Hazardous Substance

### XYLENE (MIXED ISOMERS)

## CHAMP PAVE/STRIP HIGHWAY WHITE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City -

### Hazardous Substance ZINC SULFIDE New Jersey - Workplace Hazard; New Jersey - Environmental Hazard **NFPA HMIS** HEALTH \*2 **FLAMMABILITY** 4 REACTIVITY 1 PERSONAL PROTECTION В 16. Other Information **Revision/Preparer Information** MSDS Preparer: Laura E. Radevski MSDS Preparer Phone Number: 708-865-1000 This MSDS Supercedes A Previous MSDS Dated: 09/01/2005 Disclaimer Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitablility of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information

### for their particular purposes(s).

15. Regulatory Information - Continued

Ingredient(s) - State Regulations - Continued

### Chase Products Co.

Printed Using MSDS Generator<sup>™</sup> 2000