

Page 1 of 5

CHAMPION CARPET & UPHOLSTERY FOAMING CLEANER

1. Product And Company Identification					
Supplier Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA	Manufacturer Chase Products Co. 19th and Gardner Roa Broadview, IL 60155				
Company Contact: Laura E. Radevski Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com	Company Contact: La Telephone Number: 7 FAX Number: 708-865 E-Mail: sales@chasep Web Site: www.chase	08-865-100 5-0923 roducts.com	0		
Supplier Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924	Manufacturer Emerge Chem-Tel: 1-800-255-		ts &	Phone Number	
Product Name: CHAMPION CARPET & UPHOLSTERY Chemical Name: 7-7976-2 MSDS Number: 4505 Product Code: 438-5148-7 <u>Product/Material Uses</u> - Carpet Cleaner	FOAMING CLEANER				
2. Composition/Information On Ingredients					
Ingredient Name		CAS Number		Percent Of Total Weight	
2-BUTOXYETHANOL		111-76-2	<=		1
ISOBUTANE		75-28-5			
PROPANE		74-98-6			-
SODIUM LAUROYL SARCOSINATE		137-16-6			
SODIUM LAURYL SULFATE		151-21-3			
Hazardous components, according to OSHA, are listed wh present at 0.1% or greater.	nen present at 1.0% or grea	ater. Carcino	ogen	s are listed when	

3. Hazards Identification

<u>Primary Routes(s) Of Entry</u> - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. <u>Eye Hazards</u> - Causes eye irritation.

<u>Skin Hazards</u> - Prolonged contact with skin can cause irritation. 2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may result on skin absorption of potentially harmful amounts.

Ingestion Hazards - This is an aerosol product, ingestion is unlikely to occur.

<u>Inhalation Hazards</u> - Deliberated inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea.

<u>Chronic/Carcinogenicity Effects</u> - 2-Butoxyethanol may cause hemolysis of the blood cells leading to possible liver and kidney damage. None of the ingredients, present in excess of 0.1%, are listed as carcinogenic by NTP, IARC or OSHA.

Teratogenicity (Birth Defects) - Not known

Reproductive Effects - Not known

Neurotoxicity - Not known

Mutagenicity (Genetic Effect) - Not known

<u>Signs And Symptoms</u> - Acute: Deliberated inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin can cause irritation. Irritant to eyes.

MATERIAL SAFETY DATA SHEET

CHAMPION CARPET & UPHOLSTERY FOAMING CLEANER

3. Hazards Identification - Continued

<u>Conditions Aggravated By Exposure</u> - May aggravate pre-existing skin and respiratory disorders. <u>Conditions Aggravated By Overexposure</u> - May aggravate pre-existing skin and respiratory disorders.

First Aid (Pictograms)



4. First Aid Measures

Eve - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

<u>Skin</u> - Wash skin with soap and water. If irritation develops, call a poison control center or doctor for treatment advise. <u>Ingestion</u> - Ingestion from an aerosol product is unlikely to occur.

<u>Inhalation</u> - If overcome by vapor move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

5. Fire Fighting Measures

Flash Point: Not available °F Not available °C Flash Point Method: Not available Lower Explosive Limit: Not available Upper Explosive Limit: Not available

<u>Fire And Explosion Hazards</u> - This product is an aerosol product for which **Flame Projection is 0 in.** Temperatures above 120 F may cause cans to burst.

Extinguishing Media - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

Fire Fighting Instructions - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

7. Handling And Storage

Handling And Storage Precautions - Store in a cool, dry place away from heat and open flame.

Handling Precautions - Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Keep out of reach of children.

<u>Storage Precautions</u> - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL I (NFPA-30B)** <u>Work/Hygienic Practices</u> - Wash thoroughly after handling.

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

Engineering Controls - Use with adequate general and local exhaust ventilation.

Eye/Face Protection - Conventional eyeglasses to guard against splashing.

Skin Protection - Rubber or vinyl gloves recommended.

<u>Respiratory Protection</u> - Use in well-ventilated area ONLY. When using, keep windows and doors open until fumes dissipate.

MATERIAL SAFETY DATA SHEET

CHAMPION CARPET & UPHOLSTERY FOAMING CLEANER

ACGIH TLV-TWA 20 ppm ; OSHA PEL-TWA 50 ppm (Skin) PROPANE ACGIH TLV-TWA 1000 ppm ; OSHA PEL-TWA 1,000 ppm 3. Physical And Chemical Properties Appearance - Cloudy, light yellow liquid Odor - Clean floral Chemical Type: Mixture Physical State: Liquid Melting Point: Not applicable °F Not applicable °C Boiling Point: Not applicable °F Not applicable °C Boiling Point: Not applicable °F Not applicable °C Specific Gravity: 1.00 concentrate Percent VOCs: 4.96 DH Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate 10. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.	PROPANE ACGIH TLV-TWA 1000 ppm ; OSHA PEL-TWA 1,0 9. Physical And Chemical Properties Appearance - Cloudy, light yellow liquid Odor - Clean floral	
ACGIH TLV-TWA 1000 ppm ; OSHA PEL-TWA 1,000 ppm	PROPANE ACGIH TLV-TWA 1000 ppm ; OSHA PEL-TWA 1,0 9. Physical And Chemical Properties Appearance - Cloudy, light yellow liquid Odor - Clean floral	
ACGIH TLV-TWA 1000 ppm ; OSHA PEL-TWA 1,000 ppm Appearance - Cloudy, light yellow liquid Odor - Clean floral Chemical Type: Mixture Physical State: Liquid Melting Point: Not applicable °F Not applicable °C Soliling Point: Water 212 °F Water 100 °C Specific Gravity: 1.00 concentrate Percent VOCs: 4.96 OH Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate 10. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.	ACGIH TLV-TWA 1000 ppm ; OSHA PEL-TWA 1,0 9. Physical And Chemical Properties Appearance - Cloudy, light yellow liquid Odor - Clean floral	000 ppm
Physical And Chemical Properties Appearance - Cloudy, light yellow liquid Ddor - Clean floral Chemical Type: Mixture Physical State: Liquid Melting Point: Not applicable °F Not applicable °C Boiling Point: Water 212 °F Water 100 °C Specific Gravity: 1.00 concentrate Percent VOCs: 4.96 OH Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate IO. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.	9. Physical And Chemical Properties Appearance - Cloudy, light yellow liquid Odor - Clean floral	
Appearance - Cloudy, light yellow liquid Odor - Clean floral Chemical Type: Mixture Physical State: Liquid Melting Point: Not applicable °F Not applicable °C Soiling Point: Water 212 °F Water 100 °C Specific Gravity: 1.00 concentrate Percent VOCs: 4.96 Del Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate Io. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.	Appearance - Cloudy, light yellow liquid Odor - Clean floral	
Odor - Clean floral Chemical Type: Mixture Physical State: Liquid Melting Point: Not applicable °F Not applicable °C Boiling Point: Water 212 °F Water 100 °C Specific Gravity: 1.00 concentrate Percent VOCs: 4.96 OH Factor: 9.48 Soluble in water Evaporation Rate: Faster than butyl acetate Intervention Bability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.	Odor - Clean floral	
Physical State: Liquid Melting Point: Not applicable °F Not applicable °C Boiling Point: Water 212 °F Water 100 °C Specific Gravity: 1.00 concentrate Percent VOCs: 4.96 DH Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate Intervention VO. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.		
Meiting Point: Not applicable °F Not applicable °C Boiling Point: Water 212 °F Water 100 °C Specific Gravity: 1.00 concentrate Percent VOCs: 4.96 DH Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate IO. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.		
Boiling Point: Water 212 °F Water 100 °C Specific Gravity: 1.00 concentrate Percent VOCs: 4.96 OH Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate IO. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.	Physical State: Liquid	
Specific Gravity: 1.00 concentrate Percent VOCs: 4.96 bH Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate IO. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.		
Percent VOCs: 4.96 DH Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate IO. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.	•	
 bH Factor: 9.48 Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate 10. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents. 		
Solubility: Soluble in water Evaporation Rate: Faster than butyl acetate 10. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.		
Evaporation Rate: Faster than butyl acetate 10. Stability And Reactivity Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.	Solubility: Soluble in water	
Stability: Stable Hazardous Polymerization: Will not occur Conditions To Avoid (Stability) - Temperatures above 120 F ncompatible Materials - Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.	Evaporation Rate: Faster than butyl acetate	
Conditions To Avoid (Polymerization) - Temperatures above 120 F 1. Toxicological Information	Incompatible Materials - Avoid heat, open flame an Hazardous Decomposition Products - Thermal de dioxide.	nd contact with strong alkali and strong oxidizing agents. ecomposition may yield gases like carbon monoxide and carbon
2 Ecological Information	12. Ecological Information	
Ecotoxicological Information - No specific ecological data is available for this product. Please refer to Section 6 fo nformation regarding accidental releases and Section 15 for regulatory reporting information.	Ecotoxicological Information - No specific ecologi	•
	13. Disposal Considerations	
	-	ace in trash or offer for recycling if available. If partly filled: Call
		δ.
 3. Disposal Considerations Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. 		S
 3. Disposal Considerations Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. 	your local solid waste agency for disposal instructions	
I3. Disposal Considerations Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. I4. Transport Information Proper Shipping Name - ORM-D Consumer Commodity Hazard Class	your local solid waste agency for disposal instructions	
I3. Disposal Considerations Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. I4. Transport Information Proper Shipping Name - ORM-D Consumer Commodity Iazard Class 2.1	your local solid waste agency for disposal instructions 14. Transport Information <u>Proper Shipping Name</u> - ORM-D Consumer Com <u>Hazard Class</u>	

Aerosol Consumer Commodity

CHAMPION CARPET & UPHOLSTERY FOAMING CLEANER

15. Regulatory Information

<u>U.S. Regulatory Information</u> - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard

<u>SARA Section 313 Notification</u> - This product contains the following toxic chemicals (above the *de minimis* level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

This product contains 2-Butoxyethanol. See Section 2 for % amount in the product.

Ingredient(s) - U.S. Regulatory Information

2-BUTOXYETHANOL SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

Ingredient(s) - State Regulations

2-BUTOXYETHANOL


New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

ISOBUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance



16. Other Information

<u>Revision/Preparer Information</u> MSDS Preparer: Laura E. Radevski MSDS Preparer Phone Number: 708-865-1000 This MSDS Supersedes A Previous MSDS Dated: 12/17/2007

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

MATERIAL SAFETY DATA SHEET

CHAMPION CARPET & UPHOLSTERY FOAMING CLEANER

Disclaimer - Continued

Chase Products Co.

Printed Using MSDS Generator™ 2000