

Revision Date: 08/05/2019

## SAFETY DATA SHEET

## 1. Identification

Product identifier: JINX PLUS SUPER CONCENTRATED HEAVY DUTY DEGREASER

Other means of identification

**SDS number:** RE1000000610

Recommended restrictions

Product use: Cleaner

Restrictions on use: Not known.

## Manufacturer/Importer/Distributor Information

## Manufacturer

Company Name: CLAIRE MANUFACTURING COMPANY

Address: 1000 Integram Dr

Pacific, MO 63069

Telephone: 1-630-543-7600

Fax:

Emergency telephone number: 1-866-836-8855

## 2. Hazard(s) identification

## **Hazard Classification**

**Physical Hazards** 

Flammable aerosol Category 1

**Health Hazards** 

Serious Eye Damage/Eye Irritation Category 2A

### **Label Elements**

## **Hazard Symbol:**



Signal Word: Danger

**Hazard Statement:** Extremely flammable aerosol.

Causes serious eye irritation.

Precautionary Statements



Revision Date: 08/05/2019

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face

protection.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice/attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

Hazard(s) not otherwise classified (HNOC):

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	5 - <10%
Butane	106-97-8	1 - <5%
2-Propanol	67-63-0	1 - <5%
Alcohols, C12-14-secondary, ethoxylated	84133-50-6	1 - <3%
Propane	74-98-6	1 - <5%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

**Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

**Inhalation:** Move to fresh air.

**Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get

medical advice/attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

**Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** No data available.

## 5. Fire-fighting measures



Revision Date: 08/05/2019

**General Fire Hazards:** 

Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without

risk.

#### Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

#### Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep

upwind.

Methods and material for containment and cleaning

up:

Absorb spill with vermiculite or other inert material, then place in a container

for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop

the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you

can do so without risk.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.

## 7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not

pierce or burn, even after use.

Conditions for safe storage,

including any incompatibilities:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Aerosol Level 1

#### 8. Exposure controls/personal protection

## **Control Parameters**

SDS\_US - RE1000000610



Revision Date: 08/05/2019

**Occupational Exposure Limits** 

Chemical Identity	Туре	Exposure Lin	nit Values	Source
Ethanol, 2-(2-butoxyethoxy)-	ST ESL		670 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		67 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Ethanol, 2-(2-butoxyethoxy) Inhalable fraction and vapor.	TWA	10 ppm		US. ACGIH Threshold Limit Values (03 2013)
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	800 ppm	1,900 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	AN ESL		3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		7,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	800 ppm	1,900 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		66,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		28,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
2-Propanol	REL	400 ppm	980 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	400 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	500 ppm	1,225 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm		US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	400 ppm	980 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	PEL	400 ppm	980 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	400 ppm	980 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm	1,225 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		2,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	500 ppm	1,225 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	200 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA PEL	400 ppm	980 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		492 µg/m3	US. Texas. Effects Screening Levels (Texas



Revision Date: 08/05/2019

				Commission on Environmental Quality) (11
	ST ESL		4,920 μg/m3	2016) US. Texas. Effects Screening Levels (Texas
	01 202		4,020 μg/1110	Commission on Environmental Quality) (11 2016)
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	1,000 ppm	1,800 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	1,000 ppm	1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Ethanol, 2-butoxy-	TWA	20 ppm	100 / 0	US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm	120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	5 ppm	24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm	240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	20 ppm	97 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	25 ppm	120 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		760 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		3,700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		2,900 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		600 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Ammonium hydroxide ((NH4)(OH))	AN ESL		92 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		180 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	35 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA PEL	25 ppm	18 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	STEL	35 ppm	27 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	STEL	35 ppm	27 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	35 ppm	27 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	REL	25 ppm	18 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm	35 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Acetic acid, phenylmethyl ester	TWA	10 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA PEL	10 ppm	61 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)



Revision Date: 08/05/2019

	AN ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		610 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		61 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Benzene, 1,1'-oxybis Vapor.	STEL	2 ppm		US. ACGIH Threshold Limit Values (03 2018)
·	TWA	1 ppm		US. ACGIH Threshold Limit Values (03 2018)
	PEL	1 ppm	7 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	1 ppm	7 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	REL	1 ppm	7 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	1 ppm	7 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Benzene, 1,1'-oxybis-	ST ESL		70 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		7 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Benzene, 1,1'-oxybis Vapor.	TWA	1 ppm	7 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Benzene, 1,1'-oxybis-	ST ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		1 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Phenol, 2,6-bis(1,1- dimethylethyl)-4-methyl-	TWA		10 mg/m3	US. ÓSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA		10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methylInhalable fraction and vapor.	TWA		2 mg/m3	US. ACGIH Threshold Limit Values (2008)
Phenol, 2,6-bis(1,1- dimethylethyl)-4-methyl-	REL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA PEL		10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)

**Biological Limit Values** 

Chemical Identity	Exposure Limit Values	Source
2-Propanol (acetone: Sampling time: End of shift at end of work week.)	40 mg/l (Urine)	ACGIH BEL (03 2013)
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling time: End of shift.)	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment



Revision Date: 08/05/2019

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process

enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels

to an acceptable level.

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** No data available.

Other: No data available.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

**Hygiene measures:** Avoid contact with eyes. Observe good industrial hygiene practices. When

using do not smoke.

## 9. Physical and chemical properties

**Appearance** 

Physical state: liquid

Form: Spray Aerosol
Color: No data available.

Odor: No data available.

Odor threshold: No data available.

PH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: -104.44 °C

Evaporation rate: No data available. Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

No data available.

**Vapor pressure:** 3,447.3786 - 4,826.3301 hPa (20 °C)

Vapor density:No data available.Density:No data available.Relative density:No data available.

Solubility(ies)

Solubility in water:

Solubility (other):

Partition coefficient (n-octanol/water):

No data available.

No data available.



Revision Date: 08/05/2019

8/15

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

## 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

**Conditions to avoid:** Avoid heat or contamination.

**Incompatible Materials:** No data available.

**Hazardous Decomposition** 

Products:

No data available.

## 11. Toxicological information

## Information on likely routes of exposure

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

#### Information on toxicological effects

## Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix: 21,158.42 mg/kg

**Dermal** 

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s):

Ethanol, 2-(2- LD 50 (Rabbit): 2,764 mg/kg

butoxyethoxy)-

2-Propanol LD 50: > 2,000 mg/kg

SDS\_US - RE1000000610



Revision Date: 08/05/2019

Alcohols, C12-14-LD 50: > 2,000 mg/kg

secondary, ethoxylated

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Ethanol, 2-(2-LC 50 (Various): > 20 mg/l

butoxyethoxy)-

**Butane** LC 50 (Mouse): 1,237 mg/l

2-Propanol LC 50: > 5 mg/l

LC 50: > 20 mg/l

Alcohols, C12-14-LC 50: > 5 mg/lsecondary, ethoxylated LC 50: > 20 mg/l

Propane LC 50 (Mouse): 1,237 mg/l

Repeated dose toxicity

**Product:** No data available.

Specified substance(s):

Ethanol, 2-(2-NOAEL (Rat(Female, Male), Oral, 90 d): 250 mg/kg Oral Experimental

butoxyethoxy)result, Key study

NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, 90 - 120 d): 14 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation **Butane** 

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat, Inhalation, >= 104 Weeks): 5,000 ppm(m) Inhalation 2-Propanol

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Propane

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):

Ethanol, 2-(2-

in vivo (Rabbit): Not irritant Experimental result, Supporting study butoxyethoxy)-

2-Propanol in vivo (Rabbit): Not Classified Experimental result, Key study

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):



Revision Date: 08/05/2019

10/15

Ethanol, 2-(2- Rabbit, 24 - 72 hrs: Highly irritating

butoxyethoxy)-

2-Propanol Rabbit, 1 d: Irritating.

Respiratory or Skin Sensitization

**Product:** No data available.

Specified substance(s):

Ethanol, 2-(2- Skin sensitization:, in vivo (Guinea pig): Non sensitising

butoxyethoxy)-

2-Propanol Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

**Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

## 12. Ecological information

## **Ecotoxicity:**

## Acute hazards to the aquatic environment:

Fish

**Product:** No data available.



Revision Date: 08/05/2019

Specified substance(s):

Ethanol, 2-(2- LC 50 (Lepomis macrochirus, 96 h): 1,300 mg/l Experimental result, Key

butoxyethoxy)- study

LC 50 (Pimephales promelas, 96 h): 2,400 mg/l Experimental result,

Supporting study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

2-Propanol LC 50 (Pimephales promelas, 96 h): 9,640 mg/l Experimental result, Key

study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Ethanol, 2-(2- LC 50 (Daphnia magna, 48 h): +/- 1,743 mg/l QSAR QSAR, Supporting

butoxyethoxy)- study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

2-Propanol LC 50 (Daphnia magna, 24 h): > 10,000 mg/l Experimental result, Key study

#### Chronic hazards to the aquatic environment:

Fish

**Product:** No data available.

**Aquatic Invertebrates** 

**Product:** No data available.

**Toxicity to Aquatic Plants** 

**Product:** No data available.

## Persistence and Degradability

**Biodegradation** 

**Product:** No data available.

Specified substance(s):

Ethanol, 2-(2- 85 % (28 d) Detected in water. Experimental result, Key study

butoxyethoxy)-

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

2-Propanol 53 % (5 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

**BOD/COD Ratio** 

**Product:** No data available.

**Bioaccumulative potential** 

**Bioconcentration Factor (BCF)** 

**Product:** No data available.



Revision Date: 08/05/2019

## Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Ethanol, 2-(2- No data available.

butoxyethoxy)-

Butane No data available. 2-Propanol No data available. Alcohols, C12-14- No data available.

secondary, ethoxylated

Propane No data available.

Other adverse effects: No data available.

## 13. Disposal considerations

**Disposal instructions:** Wash before disposal. Dispose to controlled facilities.

Contaminated Packaging: No data available.

## 14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): Packing Group: II
Marine Pollutant: No

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

**IMDG** 

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2 Label(s): – EmS No.:

Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):



Revision Date: 08/05/2019

Class: 2.1
Label(s): Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

## 15. Regulatory information

## **US Federal Regulations**

Restrictions on use: Not known.

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

## CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical IdentityReportable quantityButaneIbs. 1002-PropanolIbs. 100PropaneIbs. 100Ammonium hydroxide<br/>((NH4)(OH))Ibs. 1000

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## **Hazard categories**

Fire Hazard

Immediate (Acute) Health Hazards

Flammable aerosol

Serious Eye Damage/Eye Irritation

## SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

## SARA 304 Emergency Release Notification

Chemical IdentityReportable quantityEthanol,<br/>butoxyethoxy)-2-(2-ButaneIbs. 1002-PropanolIbs. 100PropaneIbs. 100

Ethanol, 2-butoxy-

Ethanol, 2-(2-

ethoxyethoxy)-

Ammonium hydroxide lbs. 1000

((NH4)(OH)) Cedrene

#### SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u> <u>Threshold Planning Quantity</u>

Ethanol, 2-(2- 10000 lbs

butoxyethoxy)-

Butane 10000 lbs



Revision Date: 08/05/2019

2-Propanol Alcohols, C12-14-	10000 lbs 10000 lbs
secondary, ethoxylated	
Propane	10000 lbs
Ethanol, 2-butoxy-	10000 lbs
Ammonium hydroxide	10000 lbs
((NH4)(OH))	
Acetic acid, phenylmethyl	10000 lbs

Acetic acid, phenylmethyl

ester Benzene, 1,1'-oxybis-Phenol, 2,6-bis(1,1-

10000 lbs 10000 lbs

dimethylethyl)-4-methyl-

SARA 313 (TRI Reporting)

Reporting Reporting threshold for threshold for manufacturing and other users processing N230 lbs N230 lbs.

**Chemical Identity** Ethanol, 2-(2butoxyethoxy)-2-Propanol

lbs lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) **US State Regulations** 

#### **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Methanone, diphenyl-Carcinogenic. 07 2012

## **US. New Jersey Worker and Community Right-to-Know Act**

## **Chemical Identity**

Ethanol, 2-(2-butoxyethoxy)-Butane

2-Propanol Propane

## **US. Massachusetts RTK - Substance List**

No ingredient regulated by MA Right-to-Know Law present.

## US. Pennsylvania RTK - Hazardous Substances

## **Chemical Identity**

Ethanol, 2-(2-butoxyethoxy)-Butane 2-Propanol Propane

#### **US. Rhode Island RTK**

No ingredient regulated by RI Right-to-Know Law present.

## International regulations

## Montreal protocol

Not applicable

#### Stockholm convention

Not applicable



Revision Date: 08/05/2019

## **Rotterdam convention**

Not applicable

#### **Kyoto protocol**

Not applicable

**Inventory Status:** 

Australia AICS: Not in compliance with the inventory.

Canada DSL Inventory List: Not in compliance with the inventory.

EINECS, ELINCS or NLP: Not in compliance with the inventory.

Japan (ENCS) List: Not in compliance with the inventory.

China Inv. Existing Chemical Substances: Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI): Not in compliance with the inventory.

Canada NDSL Inventory: Not in compliance with the inventory.

Philippines PICCS: Not in compliance with the inventory.

US TSCA Inventory: On or in compliance with the inventory

New Zealand Inventory of Chemicals: Not in compliance with the inventory.

Japan ISHL Listing: Not in compliance with the inventory.

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Mexico INSQ: Not in compliance with the inventory.

Ontario Inventory: Not in compliance with the inventory.

Taiwan Chemical Substance Inventory: Not in compliance with the inventory.

## 16.Other information, including date of preparation or last revision

**Issue Date:** 08/05/2019

**Revision Information:** No data available.

Version #: 1.0

Further Information: No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.