

MATERIAL SAFETY DATA SHEET

	1. Product and Company Iden	tification	
Product number	146-000P		
Product name	Warm Welcome		
Effective date	24-Jun-2011		
Company information	Claire Mfg. 1005 Westgate		
	Addison, IL 60101 United States		
Company phone	General Assistance 630-543-7600		
Emergency telephone US	800-424-9300		
Emergency telephone outside US	703-527-3887		
Version #	01		
	2. Hazards Identification	on	
Emergency overview	Flammable. Aerosol. CONTENTS UNDER PRESSURE. Will be easily ignited by heat, spark or flames. Harmful in contact with eyes.		
Potential health effects			
Eyes	Contact may irritate or burn eyes. Health injuries are not known or expected under normal use.		
Skin	Health injuries are not known or expected under normal use.		
Inhalation	Intentional misuse by concentrating and inhaling the product can be harmful or fatal.		
Ingestion	Exposure by ingestion of an aerosol is unlikely.		
larget organs	Central nervous system.		
Chronic effects	May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage.		
Signs and symptoms	Narcosis.		
3	. Composition / Information on	Ingredients	
Components		CAS #	Percent
Acetone		67-64-1	60 - 70
Propane		74-98-6	10 - 15
n-Butane		106-97-8	10 - 15
Non-hazardous and other components below reportable levels		2.5 - 10	
	4. First Aid Measures	5	
First aid procedures			
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.		
Skin contact	Immediately take off all contaminated of medical attention if irritation develops of		and water. Get
Inhalation	If symptoms develop move victim to free	esh air. Get medical attention	if symptoms persi
Ingestion	In the unlikely event of swallowing contact a physician or poison control center.		
·· · ·			

Notes to physician

5. Fire Fighting Measures

Symptoms may be delayed.

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media Suitable extinguishing media	Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO2).

Protection of firefighters

Protective equipment and precautions for firefighters

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures			
Methods for containment	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.		
Methods for cleaning up	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.		
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.		
7. Handling and Storage			
Handling	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid prolonged exposure.		
Storage	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.		

8. Exposure Controls / Personal Protection

osure limits ACGIH				
Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
OSHA				
Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Do not get in eyes. Wear safety glasses with side shields (or goggles).
Skin protection	Not normally needed.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	82.4 °F (27.8 °C) estimated
Color	Clear.
Density	0.7122 g/cm3 estimated
Flammability (HOC)	32.5503 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	Pleasant.
рН	Not applicable

Product name: Warm Welcome Product #: 146 Warm Welcome

Physical state	Liquid.		
Pressure	45 - 65 psig @ 70F		
Solubility	Partially		
Specific gravity	0.7123 estimated		
	10. Chemical Stability & Reactivity Information		
Chemical stability	Stable at normal conditions. Risk of ignition.		
Conditions to avoid	Heat, flames and sparks.		
Incompatible materials	Strong oxidizing agents.		
Hazardous decomposition prod			
	11. Toxicological Information		
Acute effects	Acute LD50: 28718 mg/kg estimated, Rat, Dermal Acute LC50: 105 mg/l/4h estimated, Rat, Inhalation		
Component analysis - LD50			
Toxicology Data - Selected LD			
Acetone n-Butane	67-64-1 Oral LD50 Rat 5800 mg/kg 106-97-8 Inhalation LC50 Rat 658 mg/L 4 h		
Propane	74-98-6 Inhalation LC50 Rat 658 mg/L 4 h		
Sensitization	Not expected to be hazardous by OSHA criteria.		
Teratogenicity	Not expected to be hazardous by OSHA criteria.		
	12. Ecological Information		
Ecotoxicity	LC50 7790 mg/L, Fish, 96.00 Hours, EC50 19011 mg/L, Daphnia, 48.00 Hours, Components of this product have been identified as having potential environmental concerns.		
	13. Disposal Considerations		
Waste codes			
Waste codes Disposal instructions	13. Disposal Considerations		
	13. Disposal Considerations D001: Waste Flammable material with a flash point <140 F Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all		
Disposal instructions	13. Disposal Considerations D001: Waste Flammable material with a flash point <140 F		
Disposal instructions Department of Transportation (Basic shipping requiremen	13. Disposal Considerations D001: Waste Flammable material with a flash point <140 F		
Disposal instructions Department of Transportation (Basic shipping requiremen Proper shipping name	13. Disposal Considerations D001: Waste Flammable material with a flash point <140 F		
Disposal instructions Department of Transportation (Basic shipping requiremen Proper shipping name Hazard class	13. Disposal Considerations D001: Waste Flammable material with a flash point <140 F		
Disposal instructions Department of Transportation (Basic shipping requiremen Proper shipping name Hazard class Subsidiary hazard class	13. Disposal Considerations D001: Waste Flammable material with a flash point <140 F		
Disposal instructions Department of Transportation (Basic shipping requiremen Proper shipping name Hazard class Subsidiary hazard class Additional information:	13. Disposal Considerations D001: Waste Flammable material with a flash point <140 F		
Disposal instructions Department of Transportation (Basic shipping requiremen Proper shipping name Hazard class Subsidiary hazard class	13. Disposal Considerations D001: Waste Flammable material with a flash point <140 F		

Basic shipping requirement	s:	^
Proper shipping name	AEROSOLS	
Hazard class	2.1	
UN number	1950	~
Additional information:		
Packaging exceptions	LTD QTY	
Item	5F	2
Labels required	None	
Transport Category	2	•
ΙΑΤΑ		
Basic shipping requirement	s:	A
Proper shipping name	Aerosols, flammable	
Hazard class	2.1	
UN number	1950	~
Additional information:		
Packaging exceptions	LTD QTY	
Labels required	2.1	2
Item Labels required Transport Category IATA Basic shipping requirement Proper shipping name Hazard class UN number Additional information: Packaging exceptions	5F None 2 s: Aerosols, flammable 2.1 1950 LTD QTY	2

	1	15. Regulatory Information		
US federal regulations		This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communicatior Standard, 29 CFR 1910.1200.		
Occupational Safety and Health	Administratio	n (OSHA)		
29 CFR 1910.1200 hazardou chemical	s Yes	Yes		
CERCLA (Superfund) reportable	quantity			
Acetone: 5000.0000				
Superfund Amendments and Re	authorization	Act of 1986 (SARA)		
Section 302 extremely hazardous substance	No			
Section 311 hazardous cher	nical Yes			
Hazard categories (311/312)	Delayed Fire Haz Pressure	ate Hazard - Yes Hazard - No zard - Yes e Hazard - Yes ty Hazard - No		
Inventory status				
Country(s) or region	Inventory na	ame	On inventory (yes/no)*	
China	Inventory of	Existing Chemical Substances in China (IECSC)	No	
Europe	European Inv	uropean Inventory of New and Existing Chemicals (EINECS)		
Europe	European Lis	uropean List of Notified Chemical Substances (ELINCS)		
Japan	Inventory of	ventory of Existing and New Chemical Substances (ENCS) N		
Korea	Existing Che	kisting Chemicals List (ECL)		
United States & Puerto Rico	Toxic Substa	oxic Substances Control Act (TSCA) Inventory Yes		
A "Yes" indicates that all compon	ents of this produ	uct comply with the inventory requirements administered by	the governing country(s)	
State regulations				
U.S Pennsylvania - RTK (Rigl	nt to Know) List			
Acetone n-Butane Propane	67-64-1 106-97-8 74-98-6	Environmental hazard Present Present		

16. Other Information

Further information

IMDG

HMIS® is a registered trade and service mark of the NPCA.

Disclaimer

Health: 1 Flammability: 4 Physical hazard: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

Prepared by

Regulatory Compliance