

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 155-000P
Product name Oceanic
Effective date 24-Jun-2011
Company information Claire Mfg.

1005 Westgate Addison, IL 60101 United States

Company phone General Assistance 630-543-7600

Emergency telephone US 800-424-9300 Emergency telephone outside US 703-527-3887

Version # 01

2. Hazards Identification

Emergency overview Flammable. Aerosol. CONTENTS UNDER PRESSURE.

Will be easily ignited by heat, spark or flames. Harmful in contact with eyes.

Potential health effects

Eyes Contact may irritate or burn eyes. Health injuries are not known or expected under

normal use.

Skin Health injuries are not known or expected under normal use.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Ingestion Exposure by ingestion of an aerosol is unlikely.

Target organs Central nervous system.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of

coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage.

Signs and symptoms Narcosis.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Acetone	67-64-1	60 - 70
Propane	74-98-6	10 - 15
n-Butane	106-97-8	10 - 15
Non-hazardous and other components below reportable levels		2.5 - 10

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention

immediately.

Skin contact Immediately take off all contaminated clothing. Wash off with soap and water. Get

medical attention if irritation develops or persists.

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Ingestion In the unlikely event of swallowing contact a physician or poison control center.

Notes to physician Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may

cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO2).

Product name: Oceanic MSDS US

Product #: 155 Oceanic

Protection of firefighters

Protective equipment and precautions for firefighters

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Acetone

Propane

Components	CAS#	TWA	STEL	Ceiling
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
OSHA				
Components	CAS#	TWA	STEL	Ceiling

1000 ppm

1000 ppm

Personal protective equipment

Eye / face protection

Do not get in eyes. Wear safety glasses with side shields (or goggles).

Skin protection Not normally needed.

67-64-1

74-98-6

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Not established

Not established

Not established

Not established

9. Physical & Chemical Properties

Appearance Compressed liquefied gas.

Boiling point 82.4 °F (27.8 °C) estimated

Color Clear

Density 0.7195 g/cm3 estimated **Flammability (HOC)** 32.5503 kJ/g estimated

Flash back N

Flash point -156 °F (-104.4 °C) Propellant

Form Aerosol.
Freezing point Not available
Odor Pleasant.
pH Not applicable

Product name: Oceanic MSDS US

Product #: 155-Oceanic

Physical state Liquid.

Pressure 45 - 65 psig @ 70F

Partially Solubility

Specific gravity 0.7196 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Stable at normal conditions. Risk of ignition.

Conditions to avoid Heat, flames and sparks. Strong oxidizing agents. Incompatible materials May include oxides of carbon. Hazardous decomposition products

11. Toxicological Information

Acute effects Acute LD50: 28718 mg/kg estimated, Rat, Dermal

Acute LC50: 105 mg/l/4h estimated, Rat, Inhalation

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Acetone 67-64-1 Oral LD50 Rat 5800 mg/kg n-Butane 106-97-8 Inhalation LC50 Rat 658 mg/L 4 h 74-98-6 Inhalation LC50 Rat 658 mg/L 4 h Propane Sensitization Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by OSHA criteria. **Teratogenicity**

12. Ecological Information

LC50 7790 mg/L, Fish, 96.00 Hours, **Ecotoxicity**

EC50 19011 mg/L, Daphnia, 48.00 Hours,

Components of this product have been identified as having potential environmental

concerns.

13. Disposal Considerations

D001: Waste Flammable material with a flash point <140 F Waste codes

Disposal instructions Contents under pressure. Dispose of this material and its container to hazardous or

special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all

applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Consumer commodity Proper shipping name

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306 156, 306 Packaging non bulk Packaging bulk None

Product name: Oceanic MSDS US

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS

Hazard class 2.1 UN number 1950

Additional information:

Packaging exceptionsLTD QTYItem5FLabels requiredNoneTransport Category2



IATA

Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class2.1UN number1950

Additional information:

Packaging exceptions LTD QTY
Labels required 2.1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely No

hazardous substance

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

Country(s) or regionInventory nameOn inventory (yes/no)*ChinaInventory of Existing Chemical Substances in China (IECSC)No

EuropeEuropean Inventory of New and Existing Chemicals (EINECS)NoEuropeEuropean List of Notified Chemical Substances (ELINCS)NoJapanInventory of Existing and New Chemical Substances (ENCS)NoKoreaExisting Chemicals List (ECL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone 67-64-1 Environmental hazard

 n-Butane
 106-97-8
 Present

 Propane
 74-98-6
 Present

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

Product name: Oceanic

Product #: 155·Oceanic

4 / 5

HMIS® ratings Health: 1

Flammability: 4 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and

experience currently available.

Prepared by Regulatory Compliance

Product name: Oceanic MSDS US

Product #: 155-Oceanic 5 / 5