



Product Name: Alkaline zinc manganese button battery

Applicant Name: Huizhou Yongjin environmental protection ene

rgy Co., Ltd.

Model/type: AG13\LR44

AG0\LR521, AG1\LR621, AG2\LR726, AG3\LR41, AG4\LR626, AG5\LR754\ AG6\LR920, AG7\LR927, AG8\LR1120, AG9\LR936, AG10\LR1130, AG11\LR721, AG12\LR43, AG13\LR44, 23A, 27A, 4LR44,

625A, 9V

Shenzhen ZKT Technology Co., Ltd.

Shenzhen ZKT Technolgy Co., Ltd.









Material Safety Data Sheet (MSDS)

Report Reference No.....: ZKT-2019124468S

Date of issue....: Jan. 05, 2020

Total number of pages.....:

Applicant name.....: Huizhou Yongjin environmental protection energy Co., Ltd.

Address....: Dongtai hardware factory, Qingyun private industrial zone, Huido

ng District, Huizhou City, Guangdong, China

Manufacturer name....: Huizhou Yongjin environmental protection energy Co., Ltd.

Dongtai hardware factory, Qingyun private industrial zone, Huido Address....:

ng District, Huizhou City, Guangdong, China

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Address....:

Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Test item description....: Alkaline zinc manganese button battery

Trade Mark....:

Model/Type reference.....: AG13\LR44

AG0\LR521, AG1\LR621, AG2\LR726, AG3\LR41, AG4\LR626,

AG5\LR754, AG6\LR920, AG7\LR927, AG8\LR1120, AG9\LR936, AG10\LR1130, AG11\LR721, AG12\LR43,

AG13\LR44, 23A, 27A, 4LR44, 625A, 9V

Ratings....: 1.5V, 140mAh

Weight: 1.85q

D:11.4mm Shape and Physical Dimension (mm):

T:5.09mm

Version number: V 1.2

.....

Preparation Date: Jan. 02, 2020

Revision date: Jan. 02, 2020 to Jan. 05, 2020

Signature:

Signature:

Signature

Tested by: Telec Luo

elec Lus

Compiled by: Allen Chan

rien Chan


Approved by: Michael Xie

Date: Jan. 02, 2020


Date: Jan. 02, 2020

Date: Jan. 02, 2020

Shenzhen ZKT Technolgy Co., Ltd.











Page 3 of 11

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING Product Identifier

Product name: Alkaline zinc manganese button battery

Model: AG13\LR44

AG0\LR521, AG1\LR621, AG2\LR726, AG3\LR41, AG4\LR626, AG5\LR754, AG6\LR920, AG7\LR927, AG8\LR1120, AG9\LR936, AG10\LR1130, AG11\LR721, AG12\LR43, AG13\LR44, 23A, 27A, 4LR44, 625A, 9V

Other means of identification

Synonyms:none

Recommended use of the chemical and restrictions on use

Recommended Use: Used in portabl electronic equipments; Uses advidsed against:

- a) Do not dismantle, open or shred secondary cells or batteries.
- b) Do not expose cells or batteries to heat or fire. Avoid storage in direct sunlight.
- c) Do not short-circuit a cell or a battery. Do not store cells or batteries haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.
- d) Do not remove a cell or battery from its original packaging until required for use.
- e) Do not subject cells or batteries to mechanical shock.
- f) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has been made, wash the affected area with copious amounts of water and seek medical advice.
- g) Do not use any charger other than that specifically provided for use with the equipment.
- h) Observe the plus (+) and minus (-) marks on the cell, battery and equipment and ensure correct use.
- i) Do not use any cell or battery which is not designed for use with the equipment.
- j) Do not mix cells of different manufacture, capacity, size or type within a device.
- k) Battery usage by children should be supervised.
- I) Seek medical advice immediately if a cell or a battery has been swallowed.
- m) Always purchase the battery recommended by the device manufacturer for the equipment.
- n) Keep cells and batteries clean and dry.
- o) Wipe the cell or battery terminals with a clean dry cloth if they become dirty.
- p) Primary batteries forbid to be charged before use.
- g) Retain the original product literature for future reference.
- r) Use only the cell or battery in the application for which it was intended.
- s) When possible, remove the battery from the equipment when not in use.
- t) Dispose of properly.

Details of the supplier of the safety data sheet:

Supplier Name: Huizhou Yongjin environmental protection energy Co., Ltd.

Address: Dongtai hardware factory, Qingyun private industrial zone, Huidong District, Huizhou City,

Guangdong, China

Telephone number of the supplier: 0755-29770716 Emergency Telephone No.(24h): 13728760858

Fax: 0755-29770825 Postcode: N/A

E-mail address: yjdc168@126.com

Emergency telephone number

Company Emergency Phone Number: N/A

Shenzhen ZKT Technolgy Co., Ltd.











HAZARDS IDENTIFICATION

Classification

No harm at the normal use. If contact the Electrolyte liquid in the Li-ion Battery, reference as follows:

Classification of the substance or mixture

Classification according to GHS Acute Toxicity, Oral(Hazard category 4) Acute Toxicity, Dermal(Hazard category 3) Skin, irritate(Cagegory 1B) Eye Irritate (Hazard category 1)

GHS Label elements, including precautionary statements:







GHS06

Signal word: Warning Hazard statement(s):

H242: Heating may cause a fire; H311: Toxic in contact with skin;

H314: Causes severe skin burns and eye damage;

H302: Harmful if swallowed;

precautionary statements:

Prevention:

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P312:Call a Poison center or doctor/physician if you feel unwell. P302+P350-IF ON SKIN: Gently wash with plenty of soap and water P301+P330+P331-IF SWALLOWED: rise mouth. Do NOT induce vomiting P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

None

Disposal

P501: Dispose of contents/container in accordance with local/national regulations

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

No information available.

Shenzhen ZKT Technolgy Co., Ltd.











3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Description:

Product: Consisting of the following components.

Common Chemical Name	Concentration (%)	CAS Number	EC No.	
Manganese Dioxide(MnO ₂)	42.5	1313-13-9	215-202-6	
Zinc(Zn)	17.2	7440-66-6	231-175-3	
Electrolyte (KOH solution)	8%	1310-58-3	1	
Graphite (C)	2.4%	7782-42-5		
Potassium hydroxide (KOH)	5.5	1	1	
Conductive agent	0.3	1	1	
ZnO	0.45	1	1	
Steel	15.6	1	1	
The cathode assembly	8.0	1	1	

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

FIRST-AID MEASUES

First aid measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

Shenzhen ZKT Technolgy Co., Ltd.











Page 6 of 11

FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO2, dry chemical powder, water spray. Unsuitable Extinguishing Media:No information available.

Specific Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide(CO)

Carbon dioxide

Other irritating and toxic gases.

Hazardous Combustion Products

Carbon oxides. **Explosion Data** Sensitivity to Mechanical Impact Nο Sensitivity to Static Discharge No

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

Special hazards arising from the substance or mixture:

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>100 ℃), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of

Evacuate personnel to safe areas.

Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.


Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

Shenzhen ZKT Technolgy Co., Ltd.









Page 7 of 11

HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

Wash thoroughly after handling. Use this material with adequate ventilation.

The product is not explosive.

Conditions for safe storage, including any incompatibilities

If the Battery is subject to storage for such a long term as more than 3 months, and recommended at 0°C~+35°C for long period storage.

The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.

The voltage for a long time storage shall be 1.55V~1.65V range.

Do not storage Battery haphazardly in a box or drawer where they may short-circuit each other or be shortcircuited by other metal objects.

Keep out of reach of children.

Do not expose Battery to heat or fire. Avoid storage in direct sunlight.

Do not store together with oxidizing and acidic materials.

Keep ignition sources away- Do not smoke.

Store in cool, dry and well-ventilated place.

Incompatible Products None known.

EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment **Eye/Face Protection:**



Tightly sealed goggles

Body protection:

Protective work clothing.

Skin protection:



Protective gloves

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Shenzhen ZKT Technolgy Co., Ltd.











PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Form: Cylindrical			
	Color: Orange			
	Odour: Odourless			
	Odor Threshold: No info	ormation available		
Change in condi	tion:			
pH, with indication	on of the concentration	Not determined.		
Melting point/freezing point		Not determined.		
Initial boiling point and Boiling range:		Not determined.		
Flash Point		Not determined.		
Evaporation rate		Not determined.		
Flammability (so	lid, gas)	Not determined.		
Upper/lower flammability or explosive limits		Not determined.		
Vapor Pressure:		Not determined.		
Vapor Density:		Not determined.		
relative density:		Not determined.		
Solubility in Water:		Not determined.		
Solubility in other solvents		Not determined.		
n-octanol/water partition coefficient		Not determined.		
Auto-ignition temperature		Product is not self-igniting.		
Decomposition temperature		Not determined.		
Odout threshold		Not determined.		
Evaporation rate		Not determined.		
Viscosity		Not determined.		
Other Informatio	n	No further relevant information available.		















10. STABILITY AND REACTIVITY

<u>Reactivity:</u> Stable under recommended storage and handling conditions (see section 7, Handling and storage).

Chemical stability: Stable under normal conditions of use, storage and transport.

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Possibility of Hazardous Reactions: None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to avoid: Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong base.

Hazardous Decomposition Products: Carbon oxides, Other irritating and toxic gases.

11. TOXICOLOGICAL INFORMATION

Acute toxiciy: No data available.

LD/LC50 values relevant for classification:

Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.
Respiratory or skin sensitization: No sensitizing effects known.
Specific target organ system toxicity: No information available.

CMR effects(carcinogenity, mutagenicity and toxicity for reproduction): No information available.

12. Ecological Information

Toxicity:

Acquatic toxicity:

No further relevant information available.

<u>Persistence and degradability:</u> No further relevant information available. <u>Bioaccumulative potential:</u> No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Shenzhen ZKT Technolgy Co., Ltd.

1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China



<u>=</u>

xkt@zkt-lab.com





Page 10 of 11

14. TRANSPORT INFORMATION

Land transport

ADR/RID class: Not regulated.

Maritime transport

Non-Hazardous for sea transport: Non-hazardous for sea transport.

Air transport

Not restricted to IATA DGR according to special provision A123.

The alkaline battery according to SP A 123 of the 2020 IATA Dangerous Goods regulations 61th Edition may be transported. and applicable U.S. DOT regulations for the safe transport of Panasonic alkaline battery.

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

The Nickel-cadmium rechargeable battery having the potential of a dangerous evolution of heat must be prepared for transport so as to prevent: (a) a short-circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals; or, in the case of equipment, by disconnection of the battery and protection of exposed terminals); and

(b) Accidental activation.

The words "Not Restricted" and the Special Provision number must be included in the description of the substance on the Air Waybill as required by 8.2.6, when an Air Waybill is issued.

The package must be handled with care and that a flammability hazard exists if the package is damaged;

Road (ADR/RE): not regulated Air (ICAO/IATA): not regulated Sea (IMDG): not regulated

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

Authorisations: No information available. Restrictions on use: No information available.


Regulatory information

CAS No.	EU (EINECS)	US (TSCA)	Japan (ENCS)	Canada (DSL/ NDSL)	Austrlia (AICS)	Korea (ECL)	China (IECSC)
1313-13-9	Listed	Listed	Not listed	NDSL	Not listed	Listed	Not listed
1310-58-3	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7440-66-6	Listed	Listed	Listed	DSL	Listed	Listed	Listed
12190-79-3	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
7429-90-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
24937-79-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7782-42-5	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
7440-50-8	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
9003-55-8	Listed	Listed	Listed	DSL	Listed	Listed	Listed
9002-88-4	Listed	Not listed	Not listed	Not listed	Not listed	Not listed	Listed
9003-07-0	Listed	Listed	Not listed	NDSL	Not listed	Not listed	Not listed
21324-40-3	Listed	Listed	Listed	DSL	Listed	Listed	Listed
96-49-1	Listed	Listed	Listed	DSL	Listed	Listed	Listed

Chemical safety assessment A Chemical Safety Assessment has not been carried out.

Shenzhen ZKT Technolgy Co., Ltd.













16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

R20/22: Harmful by inhalation and if swallowed.

R36: Irritating to eyes. H302: Harmful if swallowed. H332: Harmful if inhaled.

===== End of MSDS =====

Shenzhen ZKT Technolgy Co., Ltd.



+86-755-2233 6688

