# Safety Data Sheet



Revision Number: 005.0

## 1. PRODUCT AND COMPANY IDENTIFICATION

**IDH number:** 

Product name:

 Product type:
 Activa

 Restriction of Use:
 None

 Company address:
 Henkel Corporation

 One Henkel Way
 Rocky Hill, Connecticut 06067

LOCTITE SF 7387 AE known as LOCTITE® 7387 DEPEND® ACTIVATO Activator None identified

 Item number:
 21088

 Region:
 United States

 Contact information:

 Telephone:
 (860) 571-5100

 MEDICAL EMERGENCY Phone:
 Poison C

Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

209714

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW		
WARNING:	CONTENTS UNDER PRESSURE.	
	FLAMMABLE AEROSOL.	
	CAUSES SKIN IRRITATION.	
	MAY CAUSE AN ALLERGIC SKIN REACTION.	
	CAUSES SERIOUS EYE IRRITATION.	
	MAY CAUSE DROWSINESS OR DIZZINESS.	

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL.	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

	PICTOGRAM(	S)
--	------------	----



#### **Precautionary Statements**

**Prevention:** Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or spray. Wash thoroughly after handling. Use only outdoors or in a wellventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye and face protection. Wear protective gloves. **Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. Storage: IDH number: 209714 Product name: LOCTITE SF 7387 AE known as LOCTITE® 7387 DEPEND® ACTIVATO

Page 1 of 6

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding  $50^{\circ}C/122^{\circ}F$ .

### Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
n-Heptane	142-82-5	30 - 60	
Aldehyde-amine condensate	Proprietary	10 - 30	
Isobutane	75-28-5	10 - 30	
2-Propanol	67-63-0	10 - 30	
Methylcyclohexane	108-87-2	1 - 5	
Octane	111-65-9	1 - 5	

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES	
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.
5. F	IRE FIGHTING MEASURES
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Contents under pressure. Exposure to temperatures above 49°C (120°F) may cause container to burst. Do not puncture or incinerate pressurized containers.

#### Hazardous combustion products:

Oxides of carbon. Oxides of nitrogen. Hydrocarbons. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Ensure adequate ventilation. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

# 7. HANDLING AND STORAGE

Handling:	During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not puncture or incinerate pressurized containers. Refer to Section 8.
Storage:	For safe storage, store between 0 $^{\circ}$ C (32 $^{\circ}$ F) and 38 $^{\circ}$ C (100.4 $^{\circ}$ F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
n-Heptane	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m3) PEL	None	None
Aldehyde-amine condensate	None	None	None	None
Isobutane	1,000 ppm STEL	None	None	None
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
Methylcyclohexane	400 ppm TWA	500 ppm (2,000 mg/m3) PEL	None	None
Octane	300 ppm TWA	500 ppm (2,350 mg/m3) PEL	None	None

Engineering controls:	Use explosion-proof mechanical ventilation and local exhaust to control contaminants to within their occupational exposure limits during the use of this product.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.
Skin protection:	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color:	Liquid, Aerosol Amber
Odor:	Aliphatic
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	35 mm hg (20 °C (68°F))
Boiling point/range:	49 °C (120.2 °F) Approximately
Melting point/ range:	Not available.
Specific gravity:	0.7694
Vapor density:	Not available.
Flash point:	-4 °C (24.8 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	83.84 %; 645.1 g/I EPA Method 24
Viscosity:	Not available.
Decomposition temperature:	Not available.

# **10. STABILITY AND REACTIVITY**

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.
Incompatible materials:	Strong oxidizing agents. Strong acids and strong bases. Amines. Alkalis. Aldehydes. Chlorine. Halogens. Ethylene oxide. Isocyanates.
Reactivity:	Not available.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition. Store away from incompatible materials. Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F).
	11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:	May cause dizziness, incoordination, headache, nausea, and vomiting.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspirated material can enter the lungs and result in pneumonitis.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
n-Heptane	Inhalation LC50 (RAT, 4 h) = 103 mg/l	Central nervous system, Irritant
Aldehyde-amine condensate	None	No Records
Isobutane	Inhalation LC50 (RAT, 15 min) = 570000 ppm	Cardiac, Central nervous system, Lung
2-Propanol	Oral LD50 (RAT) = 5,045 mg/kg Oral LD50 (RABBIT) = 6,410 mg/kg Oral LD50 (RAT) = 4.7 g/kg Oral LD50 (RABBIT) = 8.0 g/kg Oral LD50 (RABBIT) = 5.03 g/kg Dermal LD50 (RABBIT) = 12,800 mg/kg	Allergen, Blood, Brain, Central nervous system, Irritant, Kidney, Liver, Spleen
Methylcyclohexane	None	Central nervous system, Irritant, Kidney, Liver
Octane	Inhalation LC50 (RAT, 4 h) = 118 mg/l	Central nervous system, Irritant, Lung

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
n-Heptane	No	No	No
Aldehyde-amine condensate	No	No	No
Isobutane	No	No	No
2-Propanol	No	No	No
Methylcyclohexane	No	No	No
Octane	No	No	No

### **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

Not available.

## **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Hazardous waste number:

D001: Ignitable.

Follow all local, state, federal and provincial regulations for disposal.

**14. TRANSPORT INFORMATION** 

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR) Proper shipping name:

Aerosols, flammable 2.1 UN 1950 None

International Air Transportation (ICAO/IATA)

Hazard class or division:

Identification number: Packing group:

Exceptions:

Proper shipping name: Aerosols, flammable Hazard class or division: 2.1 Identification number: UN 1950 Packing group: None ID8000, May Qualify as Consumer Commodity, (Not more than 500 ml)

Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group: Marine pollutant: Exceptions:	AEROSOLS (n-Heptane) 2.1 UN 1950 None n-Heptane Limited quantity (Not more than 1 L).			
15. REGULATORY INFORMATION				
United States Regulatory Information				
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.			
TSCA 12 (b) Export Notification:	None above reporting de minimis			
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: CERCLA Reportable quantity:	None above reporting de minimis Immediate Health, Delayed Health, Fire, Sudden Release None above reporting de minimis n-Heptane (CAS# 142-82-5) 100 lbs. (45.4 kg) Isobutane (CAS# 75-28-5) 100 lbs. (45.4 kg) 2-Propanol (CAS# 67-63-0) 100 lbs. (45.4 kg) Methylcyclohexane (CAS# 108-87-2) 100 lbs. (45.4 kg) Octane (CAS# 111-65-9) 100 lbs. (45.4 kg)			
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.			
Canada Regulatory Information				
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.			

### **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

Issue date: 05/20/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.