

Posey® Arm Slings

Arm Slings

Two models available including conventional sling in washable canvas (#7411) and padded foam (#7415) for extra comfort. #7415 Comfort Sling (one size fits all)

#7411 Conventional Sling (S, M, L)

Laundering Instructions:

Fasten all buckles before washing. Machine wash warm. Dry on low setting.





#7415

#7411

Application Instructions:

1. Push the serrated edges of the slide buckle together and thread the strap from underneath through the opening. Separate the slide buckle to create an opening and pass the strap back through the serrated edges of the buckle. (See figure 1)

2. Place the arm into the sling and slip the strap over the patient's head

3. Adjust the strap to the length needed. Tuck any excess strap back through the buckle and pull down behind the sling.

Refer to photo for proper positioning.

1. Position the arm sling in front of the patient, square section on the side of the injured arm, with the adjusting buckle facing toward the patient.

THREADING THROUGH SLID

BUCKLE Fig. 1

THREADING THROUGH SLIDI

BUCKLE

- 2. Place the injured arm into the square section until the end of the sling lines up with elbow, leaving the rest of the sling to hang down.
- 3. Bring the remainder of the sling behind the patient, and over the shoulder opposite the injured arm. Neck pad should be strap side up. Make sure the strap does not twist in this
- 4. Insert the hand of the injured arm through the round section of the sling.
- 5. Adjust the strap above the hand with the tooth buckle to the proper length. Length can be further adjusted with the buckle above the square section of the sling. Refer to photo for proper positioning.

NOTE: Consult your healthcare professional regarding which arm sling is best suited for your particular needs.

J.T. Posey Company 5635 Peck Road • Arcadia, CA 91006-0020 USA • Tel: 800-447-6739 or 626-443-3143 • Fax: 800-767-3933 or 626-443-5014 • www.posey.com EU AUTH. PERSON: (MDD 93/42/EEC) MDSS GmbH, Burckhardtstr. 1, D-30163, Hannover, Germany © 1997 J.T. Posey Company. All rights reserved. M1355 061002



Posey® Arm Slings

Arm Slings

Two models available including conventional sling in washable canvas (#7411) and padded foam (#7415) for extra comfort. #7415 Comfort Sling (one size fits all)

#7411 Conventional Sling (S, M, L)

Laundering Instructions:

Fasten all buckles before washing. Machine wash warm. Dry on low setting.





#7415

Application Instructions:

1. Push the serrated edges of the slide buckle together and thread the strap from underneath through the opening. Separate the slide buckle to create an opening and pass the strap back through the serrated edges of the buckle. (See figure 1)

2. Place the arm into the sling and slip the strap over the patient's head

3. Adjust the strap to the length needed. Tuck any excess strap back through the buckle and pull down behind the sling. Refer to photo for proper positioning.

#7415

- 1. Position the arm sling in front of the patient, square section on the side of the injured arm, with the adjusting buckle facing toward the patient.
- 2. Place the injured arm into the square section until the end of the sling lines up with elbow, leaving the rest of the sling to hang down.
- 3. Bring the remainder of the sling behind the patient, and over the shoulder opposite the injured arm. Neck pad should be strap side up. Make sure the strap does not twist in this
- 4. Insert the hand of the injured arm through the round section of the sling.
- 5. Adjust the strap above the hand with the tooth buckle to the proper length. Length can be further adjusted with the buckle above the square section of the sling. Refer to photo for proper positioning.

NOTE: Consult your healthcare professional regarding which arm sling is best suited