# SAINT-GOBAIN


# SAFETY DATA SHEET

# SECTION 1 : IDENTIFICATION

| Product Name:            |
|--------------------------|
| Product Code:            |
| UPC Number:              |
| SDS Manufacturer Number: |
| Product Use/Restriction: |
| Manufacturer Name:       |
| Address:                 |
|                          |

### Website:

General Phone Number: Emergency Phone Number: SDS Creation Date: SDS Revision Date: (M)SDS Format: Vitrified Bonded STICK Bonded Abrasives 61463685505 BA\_Vit Abrasive Product. Saint-Gobain Abrasives, Inc. 1 New Bond Street Worcester, MA 01615 www.Nortonabrasives.com 508-795-5000 508-795-5000 August 15, 2009 March 31, 2015



# SECTION 2 : HAZARD(S) IDENTIFICATION

| Signal Word:                               | Not applicable.   |
|--|---|
| GHS Class:                                 | Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200 |
| Hazard Statements:                         | Not applicable.   |
| Precautionary Statements:                  | Not applicable.   |
|  |   |
| Route of Exposure:                         | Eyes. Skin. Inhalation. Ingestion.  |
| Eye:                                       | Causes eye irritation.  |
| Skin:                                      | Causes skin irritation.   |
| Inhalation:                                | Prolonged or excessive inhalation may cause respiratory tract irritation.                     |
| Ingestion:                                 | May be harmful if swallowed. May cause vomiting.  |
| Chronic Health Effects:                    | Prolonged or repeated contact may cause skin irritation.                                      |
| Signs/Symptoms:                            | Overexposure may cause headaches and dizziness.   |
| Target Organs:                             | Eyes. Skin. Respiratory system. Digestive system.   |
| Aggravation of Pre-Existing<br>Conditions: | None generally recognized.  |
|  |   |

# SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name           | CAS#   | Ingredient Percent  | EC Num.                             |
|-------------------------|--|---|-------------------------------------|
| Silicon carbide         | 409-21-2   | 60 - 100 by weight  | 206-991-8                           |
| Amorphous Silica, Fused | 60676-86-0   | 10 - 30 by weight   | 262-373-8                           |
| Notes :                 | Actual grinding tests with<br>of respirable free Crystalli | wheels known to contain Crystalline Silica di<br>ne Silica. | d not produce any detectable amount |

### SECTION 4 : FIRST AID MEASURES

| Eye Contact:        | Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists. |
|---------------------|---|
| Skin Contact:       | Immediately wash skin with soap and plenty of water.<br>Get medical attention if irritation develops or persists.   |
| Inhalation:         | If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.   |
| Ingestion:          | If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.   |
| Note to Physicians: | Not applicable.   |
| Other First Aid:    | Not applicable.   |

### SECTION 5 : FIRE FIGHTING MEASURES

| Flash Point:                     | None.   |
|----------------------------------|---|
| Auto Ignition Temperature:       | Not applicable.   |
| Lower Flammable/Explosive Limit: | Not applicable.   |
| Upper Flammable/Explosive Limit: | Not applicable.   |
| Fire Fighting Instructions:      | Not applicable.   |
| Extinguishing Media:             | Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.  |
| Unsuitable Media:                | Not applicable.   |
| Protective Equipment:            | As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Unusual Fire Hazards:            | Not applicable.   |
| Hazardous Combustion Byproducts: | Not applicable.   |
|                                  |   |
| NFPA Ratings:                    |   |
| NFPA Health:                     | 1   |

| NFPA Ratings:      |        |
|--------------------|--------|
| NFPA Health:       | 1      |
| NFPA Flammability: | 0      |
| NFPA Reactivity:   | 0      |
| ,                  | 0<br>0 |

### SECTION 6 : ACCIDENTAL RELEASE MEASURES

Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in section 8.

Personnel Precautions:

| Environmental Precautions: | Avoid runoff into storm sewers, ditches, and waterways.  |
|----------------------------|--|
| Spill Cleanup Measures:    | Not applicable.  |
| Methods for containment:   | Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, diking or other means. Provide ventilation.  |
| Methods for cleanup:       | Clean up spills immediately observing precautions in the protective equipment section. Place into a suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water to remove trace residue. |
| Other Precautions:         | Not applicable.  |

# SECTION 7 : HANDLING and STORAGE

| Handling:          | Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.   |
|--------------------|--|
| Storage:           | Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use. |
| Hygiene Practices: | Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.  |

### SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

| Engineering Controls:        | Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment. |
|------------------------------|--|
| Eye/Face Protection:         | Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.   |
| Skin Protection Description: | Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.  |
| Respiratory Protection:      | A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible<br>under certain circumstances where airborne concentrations are expected to exceed exposure limits.<br>Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if<br>there is any potential for an uncontrolled release, exposure levels are not known, or any other<br>circumstances where air purifying respirators may not provide adequate protection.                              |
| Other Protective:            | Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.   |
| PPE Pictograms:              |  |

### EXPOSURE GUIDELINES

| Ingredient                 | Guideline OSHA  | Guideline NIOSH                     | Guideline ACGIH  | Quebec Canada                                       | Ontario Canada   |
|----------------------------|---|-------------------------------------|--|---|--|
| Silicon carbide            | PEL-TWA: 15 mg/m3<br>Total particulate/dust<br>(T)<br>PEL-TWA: 5 mg/m3<br>Respirable fraction (R) |                                     | TLV-TWA: 10 mg/m3<br>Inhalable fraction (I)<br>TLV-TWA: 3 mg/m3<br>Respirable fraction (R)<br>TLV-TWA: 0.1 f/cc<br>Respirable fraction (R) | VEMP-TWA: 10<br>mg/m3 Total<br>particulate/dust (T) | OEL-TWAEV: 3<br>mg/m3 Respirable<br>fraction (R)<br>OEL-TWAEV: 10<br>mg/m3 Inhalable<br>fraction (I)<br>OEL-TWAEV: 0.1 f/cc<br>Respirable fraction (R) |
| Amorphous Silica,<br>Fused | OSHA PEL-TWA 0.1<br>mg/m3   | REL-TWA: 0.05<br>mg/m3 (Respirable) | ACGIH TLV-TWA 0.1<br>mg/m3   | VEMP-TWA: 0.1<br>mg/m3 Respirable<br>fraction (R)   | OEL-TWAEV: 0.1<br>mg/m3 Respirable<br>fraction (R)   |
| Ingredient                 | Alberta Canada  | Mexico                              | British Columbia<br>Canada   |   |  |

| Silicon carbide            | OEL-TWA: 10 mg/m3 | LMPE-PPT: 10 mg/m3<br>LMPE-CT: 20 mg/m3       | OEL-TWA: 10 mg/m3<br>Inhalable fraction (I)<br>OEL-TWA: 3 mg/m3<br>Respirable fraction (R)<br>OEL-TWA: 0.1 f/cc<br>Respirable fraction (R) |  |
|----------------------------|-------------------|---|--|--|
| Amorphous Silica,<br>Fused |                   | MPE-PPT: 0.1 mg/m3<br>Respirable fraction (R) |  |  |

# SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

| Physical State Appearance:                | Solid article.   |
|---|--|
| Color:                                    | Not determined.  |
| Odor:                                     | Odorless.  |
| Odor Threshold:                           | Not determined.  |
| Boiling Point:                            | Not determined.  |
| Melting Point:                            | Not determined.  |
| Density:                                  | Not determined.  |
| Solubility:                               | Not determined.  |
| Vapor Density:                            | Not determined.  |
| Vapor Pressure:                           | Not determined.  |
| Evaporation Rate:                         | Not determined.  |
| pH:                                       | Not determined.  |
| Viscosity:                                | Not determined.  |
| Coefficient of Water/Oil<br>Distribution: | Not determined.  |
| Flammability:                             | Not determined.  |
| Flash Point:                              | None.  |
| Auto Ignition Temperature:                | Not applicable.  |
| Explosive Properties:                     | Excessive dust accumulation could present a potential combustible dust hazard. |
| VOC Content:                              | Not determined.  |
|   |  |

# SECTION 10 : STABILITY and REACTIVITY

# SECTION 11 : TOXICOLOGICAL INFORMATION

Acute Toxicity:

This product has not been tested for its toxicity.

| Carcinogens:            |            |                     |         |         |         |  |         |
|-------------------------|------------|---------------------|---------|---------|---------|--|---------|
|                         | ACGIH      | NIOSH               | OSHA    | IARC    | NTP     |  | MEXICO  |
| Silicon carbide         | Not listed |                     |         |         |         |  |         |
| Amorphous Silica, Fused | No Data    | NIOSH<br>carcinogen | No Data | No Data | No Data |  | No Data |

| <u>Silicon carbide</u> :  |   |
|---------------------------|---|
| RTECS Number:             | "VW0450000"   |
| Inhalation:               | No Data   |
| Amorphous Silica, Fused : |   |
| RTECS Number:             | "VV7328000"   |
| Inhalation:               | Inhalation - Rat TCLo: 197 mg/m3/6H/26W (Intermittent) [Lungs, Thorax, !or Respiration - Changes in<br>lung weight] (RTECS) |

### SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity:

Please contact the phone number or address of the manufacturer listed in Section 1 for information on ecotoxicity.

### SECTION 13 : DISPOSAL CONSIDERATIONS

### Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

### SECTION 14 : TRANSPORT INFORMATION

### SECTION 15 : REGULATORY INFORMATION

### **Inventory Status**

|                         | EINECS Number | Canada DSL | TSCA Inventory<br>Status |  |
|-------------------------|---------------|------------|--------------------------|--|
| Silicon carbide         |               | Listed     | Listed                   |  |
| Amorphous Silica, Fused | 262-373-8     | Listed     | Listed                   |  |

### Amorphous Silica, Fused :

Canada IDL:

Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.1404(1487)

### Silicon carbide :

c

EC Number:206-991-8Amorphous Silica, Fused :262-373-8

### State Right To Know

|                         | RI     | PA     | MA     |  |
|-------------------------|--------|--------|--------|--|
| Silicon carbide         |        | Listed | Listed |  |
| Amorphous Silica, Fused | Listed |        | Listed |  |

# SECTION 16 : ADDITIONAL INFORMATION

| HMIS Ratings:        |   |                 |
|----------------------|---|-----------------|
| HMIS Health Hazard:  | 1 |                 |
| HMIS Fire Hazard:    | 1 |                 |
| HMIS Reactivity:     | 0 |                 |
| SDS Creation Date:   |   | August 15, 2009 |
| SDS Revision Date:   |   | March 31, 2015  |
| MSDS Revision Notes: |   | GHS Update      |
| SDS Format:          |   |                 |

 $\mathsf{Copyright} \circledast$  1996-2015 Actio Corporation. All Rights Reserved.