



MATERIAL SAFETY DATA SHEET

1. We would like to inform our customers that these batteries are exempt articles and are not subject to the 29 CFR 1910.1200 OSHA requirement, or to the Canadian WHMIS requirements and the sheets are supplied as a service to you. For other MSDSs and related information, visit: <http://www.rayovac.com/technical/msds.htm>.

1. IDENTIFICATION

PRODUCT NAME: Nickel Metal Hydride Batteries

SIZES: All

EMERGENCY TELEPHONE NUMBER: 800-424-9300 (24 hr, Chemtrec)

Environmental Health & Safety Information: 608-275-2482

EDITION DATE: 07-19-2010

APPROVED BY: Kevin J. Domack

2. INGREDIENTS

INGREDIENT NAME	CAS #	%	TLV*
Nickel and compounds	7440-02-0	30-40	1.0 mg/m ³ (Soluble Compounds, TWA)
Steel	--	15 - 25	--
Potassium Hydroxide	1310-58-3	10-15	Not Listed (for solution)
Cobalt and compounds	7440-48-4	4-8	0.1 mg/m ³ (TWA)
Manganese	7439-96-5	<2	C5.0 mg/m ³ (TWA)
Aluminum	7429-90-5	<1	15 mg/m ³ (Total Dust, TWA)
Lanthanides, Zinc	7440-66-6(Zn)	5 - 20	5 mg/m ³ (ZnO, Fume, TWA)
Water, paper, plastic, other	--	Balance	--

*Source: OSHA 29 CFR 1910.1000 Table Z-1, 2 or 3 3-01-2010

3. PHYSICAL DATA

Boiling Point @ 760 mm Hg (°C):	NA
Vapor Pressure (mm Hg @ 25°C):	NA
Vapor Density (Air = 1):	NA
Density (grams/cc):	NA
Percent Volatile by Volume (%):	NA
Evaporation Rate (Butyl Acetate = 1):	NA
Physical State:	NA
Solubility in Water (% by Weight):	NA
pH:	NA
Appearance and Odor:	geometric solid object

4. FIRE & EXPLOSION HAZARD DATA

<u>FLASH POINT:</u>	NA	<u>LOWER (LEL):</u>	NA
<u>FLAMMABLE LIMITS IN AIR (%):</u>	NA	<u>UPPER (UEL):</u>	NA
<u>EXTINGUISHING MEDIA:</u>	Use water, foam or dry powder, as appropriate.		
<u>AUTO-IGNITION:</u>	NA		

SPECIAL FIRE FIGHTING PROCEDURES: As with any fire, wear self-contained breathing apparatus to avoid inhalation of hazardous decomposition products (See section 2).

SPECIAL FIRE EXPLOSION HAZARDS: Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials.

5. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE (TLV) AND SOURCE: NA

EFFECTS OF OVEREXPOSURE: None. (In fire or rupture situation see section 2 and section 4)

EMERGENCY FIRST AID PROCEDURES:

Skin and Eyes:

In the event that battery ruptures, flush exposed skin with copious quantities of flowing lukewarm water for a minimum of 15 minutes. Get immediate medical attention for eyes. Wash skin with soap and water.

Swallowing: If you or your doctor suspects that a battery has been ingested-for assistance in the US call the NATIONAL BATTERY INGESTION HOTLINE any time at (202) 625-3333; in Canada call 416-813-5900.

For more information, visit: <http://www.nema.org/gov/ehs/committees/drybat/>

6. REACTIVITY DATA

<u>STABLE OR UNSTABLE:</u>	Stable
<u>INCOMPATIBILITY (MATERIALS TO AVOID):</u>	NA
<u>HAZARDOUS DECOMPOSITION PRODUCTS:</u>	NA
<u>DECOMPOSITION TEMPERATURE (0°F):</u>	NA
<u>HAZARDOUS POLYMERIZATION:</u>	Will Not Occur
<u>CONDITIONS TO AVOID:</u>	Avoid electrical shorting.

7. SPILL OR LEAK PROCEDURES

PROCEDURES TO CONTAIN AND CLEAN UP LEAKS OR SPILLS: In the event of a battery rupture, prevent skin contact and collect all released material in a plastic lined metal container.

REPORTING PROCEDURE: Report all spills in accordance with Federal, State and Local reporting requirements.

WASTE DISPOSAL METHOD: Waste Nickel Metal Hydride Batteries are NOT considered a USEPA Hazardous Waste. Their collection and recycling are not required under US Federal Law. Contact your battery distributor for details regarding recycling and disposal options or visit: <http://www.rbr.org>. For additional information on disposal or recycling options, visit: <http://www.nema.org/gov/ehs/committees/drybat/>

8. PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NA

VENTILATION:

Local Exhaust:	NA
Mechanical (General):	NA
Special:	NA
Other:	NA

PROTECTIVE GLOVES: NA

EYE PROTECTION: NA

OTHER PROTECTIVE CLOTHING: NA

9. SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Store in a dry place. Storing unpackaged cells together could result in cell shorting and heat build-up.

TRANSPORTATION-SHIPPING: These are considered dry-cell batteries and they are non-dangerous goods for transportation.

USDOT – See Special Provision 130

IMDG/Ocean – Not listed

ICAO/Air – See Special Provision A123. It also states to put the words “not restricted” and special provision A123 on the air waybill when an air waybill is issued.

10. SARA 313

Notification is not required because these products are article(s) that do not release a covered toxic chemical under the normal conditions of processing or use.

NOTICE: The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Rayovac Corporation makes no warranty expressed or implied.