


G604T2



SPECIAL FEATURES:

- Modern co-material goggle provides superior protection against dust entry and chemical splash
- Thermoplastics (TPE) body with universal nose bridge is flexible and contours to the user's face.
- Polycarbonate lens provides impact resistance against flying particles.
- Indirect ventilation system prevents fogging by providing a sufficient outlet for body heat.
- Two strap options (see the component list in red) for user to interchange; the cloth strap for regular usage & the plastic strap for chemical protection. It is particularly suitable for clean rooms for its lint-free material.
- Both straps are flame-retardant

GENERAL SPECIFICATIONS:

Lens thickness: 2.3mm Bridge: 45mm

PD: 68mm Overall length (lens-tip): 90mm

Lens Base: 6 curve Overall Width: 160 mm

Weight: 84gm Closest point between lens: n/a

Lens size vertical: 74.1mm Closest point between strap holding parts: 150mm

Lens size diagonal: 167mm Strap Length: 540mm

FRAME & LENS OPTIONS:

Frame colors: Light gray frame body with dark gray soft flange

Lens options: Clear, Gray

| COMPONENT | | MATERIAL | FEATURES |
|-----------------|---------------------------|---------------|---|
| Lens | | Polycarbonate | 6 base Single lens |
| Body | Hard piece | PP | Co-material body with flexible soft flange contour |
| | Soft piece | TPE | to face |
| Frame insert | | TPV | Soft insert with 6 holes engaged between lens and frame body to make indirect vents for airflow |
| Strap holder | Cloth strap (option 1) | Nylon | Strap sewed with quick-released parts |
| | Plastic strap (option 2) | NR + SBR | Strap clipped on the holder |
| Nose piece | | TPE | Universal, integral to frame body (soft piece) |
| Headban | nd Cloth strap (option 1) | Polyester | Adjustable quick-released textile elastic fixed on strap holders |
| | Plastic strap (option 2) | | Flexible plastic strap clipped on strap holders |

MARKINGS:

Lens: As per specification Frame: As per specification

PACKAGING:

1 pc in a Hi-density PE bag 1 pc per display box 72 pcs in an outer carton

STANDARDS:

Meets ANSI, CE, and CSA Certificate EN166 1BT 3 4